

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 87240
District II
811 South First, Artesia, NM 87210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised March 25, 1999

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

WELL API NO. 30-025-28847
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. NM5188
7. Lease Name or Unit Agreement Name: Strip 26 State
8. Well No. 1
9. Pool name or Wildcat Und. San Andres

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other	2. Name of Operator EOG Resources, Inc.
3. Address of Operator P.O. Box 2267 Midland, TX 79702	4. Well Location Unit Letter G : 2310 feet from the North line and 2310 feet from the East line Section 26 Township 18S Range 34E NMPM County Lea
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 3983.2 GR	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

- REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☒
CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

12/09/02 MIRU
12/10/02 Shut down for rig repairs
12/16/02 POH w/ 2 3/8" tbg. RIH w/ CIBP & set @ 4800'. Tag CIBP @ 4800'. Pumped 42 bbls brine to establish circulation.
12/17/02 RIH & spot 25 sx cement from 4800' to 4650'. POH. Weld on 5 1/2" pull nipple. Casing free @ 3800'.
12/18/02 POH w/ 5 1/2" casing. RIH & spot 100 sx cement from 4100' to 3800'. POH.
12/19/02 RIH & tag cement @ 3688'. POH to 1850'. Spot 40 sx cement from 1850' to 1750'. POH to 400'. Spot 45 sx cement from 400' to 300'. WOC. RIH & tag cement @ 300'. POH to 15'. Spot 10 sx cement from 15' to surface.
Cut off wellhead and weld on P&A marker. Clean and restore location.

Approved as to plugging of the Well Bore.
Liability under bond is retained until surface restoration is completed.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Stan Wagner TITLE Regulatory Administrator DATE 1/16/03

Type or print name Stan Wagner

Telephone No. 915 686 3689

(This space for State use)

APPROVED BY GARY W. WINK TITLE OC FIELD REPRESENTATIVE II/STAFF MANAGER DATE JAN 22 2003
Conditions of approval, if any: