

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
LG 1543	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Cities Service Oil and Gas Corporation		8. Farm or Lease Name State DW
3. Address of Operator P.O. Box 1919 - Midland, Texas 79702		9. Well No. 9
4. Location of Well UNIT LETTER <u>L</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>12</u> TOWNSHIP <u>18S</u> RANGE <u>33E</u> NMPM.		10. Field and Pool, or Wildcat (Bone) Mescalero Escarpe Spring
15. Elevation (Show whether DF, RT, GR, etc.) 4027' GR		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

TEMPORARILY ABANDON ☐

PULL OR ALTER CASING ☐

OTHER ☐

PLUG AND ABANDON ☐

CHANGE PLANS ☐

OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

COMMENCE DRILLING OPNS. ☐

CASING TEST AND CEMENT JOB ☒

OTHER ☐

ALTERING CASING ☐

PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

T.D. 9050' Lime, Shale and Chert. Waiting on completion unit. Drilled a 7-7/8" hole from 3150' to a T.D. of 9050' in Lime, Shale and Chert. Ran and set 159 Jts (6584.30') 5-1/2" OD 15.5# and 56 Jts (2466.59') 5-1/2" OD 17# casing @ 9048' and cemented w/1300 sacks of Halco Lite w/0.25# flocele & 0.5 of 1% Halad 9/sack and 315 sacks of Class H 50/50 Pozmix A w/3# salt & 0.3 of 1% Halad 22A/sack cement. PD @ 0350 CST On 11-8-84. Cement did not circulate to the surface. WOC 4 hrs. Ran temp. suvey. TOC @ 3100'. ND BOP's, set slips and NU WH.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Elmer Startz

TITLE Reg. Opr. Mgr. - Prod.

DATE 11-12-84

APPROVED BY

TITLE

DATE

NOV 15 1984

CONDITIONS OF APPROVAL, IF ANY: