

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
LG 1543	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Drilling		7. Unit Agreement Name
2. Name of Operator Cities Service Oil and Gas Corporation		8. Farm or Lease Name State DW
3. Address of Operator P.O. Box 1919 - Midland, Texas 79702		9. Well No. 9
4. Location of Well UNIT LETTER <u>L</u> <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>660</u> FEET FROM THE <u>West</u> LINE, SECTION <u>12</u> TOWNSHIP <u>18S</u> RANGE <u>33E</u> NMPM.		10. Field and Pool, or Wildcat (Bone Mescalero Escarpe Sprin
15. Elevation (Show whether DF, RT, GR, etc.) 4027' GR		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

T.D. 3150' Anhydrite. Prep to drill ahead. Drilled an 11" hole from 344' to a T.D. of 3150' in Anhydrite. Ran and set 52 Jts (2183.25') 8-5/8" OD 24# and 22 Jts (959.65') 8-5/8" OD 32# casing @ 3141' and cemented w/1000 sacks of TLW w/15# salt, 5# gilsonite & 0.25# flocele/sack + 300 sacks of Class C neat cement. PD @ 0145 CDT on 10-19-84. Circulated 150 sacks of cement to the surface. WOC 18 hrs. Tested 8-5/8" OD casing to 1000# for 30 min. - OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Elmer Startz</u>	TITLE <u>Reg. Opr. Mgr. - Prod.</u>	DATE <u>10-23-84</u>
ORIGINAL SIGNED BY <u>ELMER STARTZ</u>		
APPROVED BY <u>ELMER STARTZ</u>	TITLE <u></u>	DATE <u>OCT 25 1984</u>
CONDITIONS OF APPROVAL, IF ANY:		

RECEIVED

OCT 24 1984

C.I.B.
HODAL OFFICE