

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT  
NEW MEXICO 88240

SUBMIT IN TRIPLICATE  
(Other instructions on re-  
verse side)

Form approved  
Budget Bureau No. 1004-0135  
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER INJECTOR	7. UNIT AGREEMENT NAME N. HOBBS (G/SA) UNIT
2. NAME OF OPERATOR SHELL WESTERN E&P INC.	8. FARM OR LEASE NAME SECTION 30
3. ADDRESS OF OPERATOR P.O. BOX 991, HOUSTON, TX 77001	9. WELL NO. 443
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1300' FSL & 160' FEL	10. FIELD AND POOL, OR WILDCAT HOBBS (G/SA)
14. PERMIT NO. NA	11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA SEC. 30, T18S, R38E
15. ELEVATIONS (Show whether of, RT, GL, etc.) 3657.5' DF; 3647.5' GL	12. COUNTY OR PARISH LEA
	13. STATE NEW MEXICO

6. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PLUG OR ALTER CASING

MULTIPLE COMPLETE

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) COMPLETED AS AN INJECTOR

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)

7. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

1-18-85: Spotted 250 gals 15% HCl-NEA from 4050' to 4247'. Perf'd from top down 4094' to 4247' (38 holes). Cleaned out to 4290'.

1-21 to 1-22-85: Drilled out DV tool @ 3058' and float collar @ 4270'. Acidized San Andres perf's 4094' to 4247' w/5700 gals 15% HCl-NEA.

1-23-85: Set 5-1/2" Guiberson Uni-Pkr VI @ 4024' w/12,000# tension. Pressure tested packer & 5-1/2" csg to 500 psi, held OK. Nipple up well head.

1-26-85: Started well injecting.

I hereby certify that the foregoing is true and correct

SIGNED A. J. FORE

TITLE SUPERVISOR REG. & PERMITS

DATE MARCH 28, 1985

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY [Signature]  
CONDITIONS OF APPROVAL IF ANY

TITLE \_\_\_\_\_

DATE \_\_\_\_\_

APR 2 1985

\*See Instructions on Reverse Side

CARLSBAD, NEW MEXICO