

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
LG 1543	

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT TO DRILL" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input checked="" type="checkbox"/> Drilling		7. Unit Agreement Name
2. Name of Operator Cities Service Oil and Gas Corporation		8. Farm or Lease Name State DW
3. Address of Operator P.O. Box 1919 - Midland, Texas 79702		9. Well No. 10
4. Location of Well UNIT LETTER <u>N</u> <u>990</u> FEET FROM THE <u>South</u> LINE AND <u>2130</u> FEET FROM THE <u>West</u> LINE, SECTION <u>12</u> TOWNSHIP <u>18S</u> RANGE <u>33E</u> NMPM.		10. Field and Pool, or Wildcat (Bone Mescalero Escarpe Sprin
15. Elevation (Show whether DF, RT, GR, etc.) 4031' GR		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK	<input type="checkbox"/>
TEMPORARILY ABANDON	<input type="checkbox"/>
PULL OR ALTER CASING	<input type="checkbox"/>
OTHER	<input type="checkbox"/>

PLUG AND ABANDON	<input type="checkbox"/>
CHANGE PLANS	<input type="checkbox"/>
OTHER	<input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK	<input type="checkbox"/>	ALTERING CASING	<input type="checkbox"/>
COMMENCE DRILLING OPNS.	<input checked="" type="checkbox"/>	PLUG AND ABANDONMENT	<input type="checkbox"/>
CASING TEST AND CEMENT JOB	<input checked="" type="checkbox"/>	OTHER	<input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

T.D. 350' Surface Rock. Prep to drill ahead. MIRU a rotary and spudded a 17-1/2" hole @ 2345 CST on 11-12-84 and drilled to a T.D. of 350' in Surface Rock. Ran and set 8 Jts (352.29' of 13-3/8" OD 48# casing @ 350' and cemented w/300 sacks of TLW w/0.25# flocele & 2% CaCl₂/sack + 200 sacks of Class C w/2% CaCl₂/sack cement. PD @ 1015 CST on 11-13-84. Circulated 50 sacks of cement of the surface. WOC 18 hrs. Tested 13-3/8" OD casing to 800# for 30 min. - OK.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED <u>Edmer Startz</u>	TITLE <u>Reg. Opr. Mgr. - Prod.</u>	DATE <u>11-14-84</u>
ORIGINAL COPIES BY <u>FOR</u> <u>TRAIN</u>		
APPROVED BY <u>DEPT. OF</u> <u>SAFETY</u>	TITLE <u></u>	DATE <u>NOV 16 1984</u>
CONDITIONS OF APPROVAL, IF ANY:		