

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

**OIL CONSERVATION DIVISION**  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.  
30-025-29025

5. Indicate Type of Lease  
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.  
V-1091

**SUNDRY NOTICES AND REPORTS ON WELLS**  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:  
OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. Name of Operator  
Anadarko Petroleum Corporation

3. Address of Operator  
P. O. Drawer 130, Artesia, NM 88210

4. Well Location  
Unit Letter P : 660 Feet From The South Line and 660 Feet From The East Line

Section 15 Township 18S Range 35E NMPM Lea County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)  
3897' GR

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

**NOTICE OF INTENTION TO:**

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐  
OTHER: ☐

**SUBSEQUENT REPORT OF:**

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐  
CASING TEST AND CEMENT JOB ☐  
OTHER: Re-entry & P & A ☒

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

8. Perforated 4 squeeze holes 5008' and 400'. Set packer at 4697'. Attempted to establish circulation up 9-5/8" casing. Could not. At 3000#, was pumping into formation below 9-5/8" casing shoe. Cement squeezed with 25 sx Class H with 3% CaCl. Waited and then tagged top of plug @ 4865'. (This plug covers 9-5/8" casing shoe)
9. Perforated 4 squeeze holes @ 3940'. (100' below salt) Set packer at 3670' and pressured to 3000#. Held. No circulation. TOH. Perforated 4 squeeze holes @ 1700' (top of salt). Set packer at 3670' and pressured to 3000#. Held. No circulation. TOH. Perforated 4 squeeze holes @ 3640'. Set packer @ 3670' and pressured to 3000#. Held. Still could not break circulation. Spotted 25 sx Class H with 3% CaCl @ 4008'. Waited and tagged top of plug at 3803'. (This plug covers base of salt).

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mike Baswell TITLE Field Foreman DATE 3/7/89

TYPE OR PRINT NAME Mike Baswell TELEPHONE NO. 748-3368

(This space for State Use)

APPROVED BY R. Adair TITLE OIL & GAS INSPECTOR DATE MAY 16 1989

CONDITIONS OF APPROVAL, IF ANY: