

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPPLICATE\*  
(Other instructions on reverse side)

Budget Bulletin No. 1004-1.05  
Expires August 31, 1985

5. PHASE DESIGNATION AND SERIAL NO.

NM-0245247

6. INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT" for such proposals.)

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

McElvain

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

EK Bone Springs

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Sec. 25, T18S, R33E

12. COUNTY OR PARISH 13. STATE

Lea

NM

OIL ☒ WELL ☒ GAS ☐ WELL ☐ OTHER

2. NAME OF OPERATOR

C. W. Trainer

3. ADDRESS OF OPERATOR

P. O. Box 755, Hobbs, New Mexico 88241

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*

See also space 17 below.)

At surface 660' FSL & 810' FWL of Sec. 25

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3830.6 GL

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

Other:

PULL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON\*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

REPAIRING WELL

ALTERING CASING

ABANDONMENT\*

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. REE. PROPOSED OR COMPLETED OPERATIONS: (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Work began 12/26/85. Pull rods & tubing. Clean out to 9949 with sand pump. Perf 9490 to 9855 with 42 holes. Ran scab liner to blank off old perfs 9470-78. Treat with 4,000 gallons 7 1/2% SRA acid. Swab load. Frac down 5 1/2" casing with 94,400 gallons 70 quality CO<sub>2</sub> foam & 170,000# 20/40 sand. Pull scab liner. Swab & flow load. Ran tubing rods & pump. 1/16/86 pump 66 bbls oil and 30 bbls water in 24 hours.

ACCEPTED FOR RECORD

*gwd*  
JAN 28 1986

CARLSBAD, N.M. 88502

I hereby certify that the foregoing is true and correct

SIGNED

*William Haller*

TITLE Agent

DATE 1/20/86

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side

RECEIVED

JAN 27 1986

C.C.D.  
HOBBS OFFICE