

- 31. (a) 7659, 7667, 7711, 7712, 7760, 7762 1/2, 7765, 7775 1/2, 7779, 7781, 7796, 7799, 7802 1/2, 7808 1/2, 7817 1/2, 7830, 7877, 7891, 7906 1/2, 7919 1/2, 7929, and 7932 1/2 (22 Holes)
- 32. (a) 20,000 gallons jelled 20% NE-FE acid/50 quality nitrogen foam. Four stages with salt CIBP at 7500'.
- 31. (b) 6710 1/2, 6711 1/2, 6716 1/2, 6717 1/2, 6722, 6724 1/2, 6727 1/2, 6733, 6734, 6739, 6740, 6743, 6744, 6750, 6751, 6754, 6755, 6764, 6776 1/2, 6777 1/2, and 6783 1/2 (21 Holes)
- 32. (b) 6000 gallons 15% NE-FE acid. Squeezed with 163sx Class H.
- 31. (c) 6405, 6406, 6417 1/2, 6418 1/2, 6421, 6422, 6425, 6426, 6431, 6435 1/2, 6437, 6441, 6442, 6449, 6450, 6485, 6486, 6510, 6513, and 6514 (20 Holes)
- 32. (c) 6000 gallons 15% NE-FE acid. Squeezed with 156sx Class H.
- 31. (d) 6088 - 6106 @ 1 SPF (19 Holes)
- 32. (d) Squeezed with 25sx Class H.
- 31. (e) 5954 - 5963 @ 1 SPF (10 Holes)
- 32. (e) 1500 gallons 15% NE-FE.
- 31. (f) 7113 1/2, 7114 1/2, 7117, 7118, 7119, 7126, 7127, 7130, 7131, 7134, 7135, and 7137 (12 Holes)
- 32. (f) 3000 gallons 15% NE-FE acid.