orm 3160-5 lovember 1983) formerty 9-331) DEP	UNITED STA ARTMENT F TH	ITES IE INTERIC	BUBMIT IN TRI (Other instruction) R verse side)	onso -i	Expires August	
- · · · · · · · · · · · · · · · · · · ·	UREAU OF LAND MA	NAGEMENT			NM-0245247	
HOURS SUNDRY NOTICES AND REPORTS ON WELLS				6.	6. IF INDIAN, ALLOTTER OR TRIBE NAME	
(Do not use this form for	proposals to drill or to de	eepen or plug bac	rk to a different recerv	roir.		
Use "A	PPLICATION FOR TEXAL!				UNIT AGREEMENT NA	MB
OIL WELL WELL OTHER RAME OF OPERATOR Manzano Oil Corporation (505-623-1996) B. ADDRESS OF OPERATOR P.O. Box 571/Roswell, NM 88202 E. Location of Well (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 2130' FNL & 1980' FEL of Section 25					8. FARM OR LHABE HAME Edith Federal 9. WELL BO. 2 10. FIELD AND POOL, OR WILDCAT Undes EK Bone Springs 11. EEC., T., R., M., OR BLK. AND	
				8.		
				9.		
				10		
				11		
2130 THE & 1300	, , , , , , , , , , , , , , , , , , , ,	. •			SURVEY OR AREA	
					Sec 25,T189	
PERMIT NO.	15. SLEVATIONS (S	3882 ("	Lea	New Mexic
					- D-t-	
	ck Appropriate Box To	o Indicate Na	nure or Monce, Re		E EXIC	
			WATER SHUT-OFF		REPAIRING V	ratz.
FRACTURE TREAT	FOLL OR ALTER CASIS MULTIPLE COMPLETE		PRACTURE TREAT	MENT	ALTERING C	
SHOOT OR ACIDISS	ABANDON®		SHOOTING OR ACI		ABANDORME	· I——I
REPAIR WELL	CHANGE PLANS				<u>ermediate:ca:</u>	
(Other)	, 7		Completion	or Recomplette	multiple completion a Report and Leg for	PML.)
	ter or success forces of	acc are barranes.	accessor, was fire bere		mathe des all markes	
2/3/85 Spudded 1	TED OPERATIONS (Clearly etc directionally drilled, give a $7\frac{1}{2}$ " hole at 11:0 13-3/8" casing.	00 a.m. 2/3	3/85 and dril	• .		
2/3/85 Spudded 1 cemented 2/12/85 Drilled t casing. 1/4# flos 2% CaCl. Press plu	7½" hole at 11:0	oo a.m. 2/3 See previous (3701 at 3700 to per sack sacks to said 0K.	3/85 and drilious report73') 8-5/8" 2 with 1300 sad	led to 350 24# and 33 cks Hallil 300 sacks	O' and ran an 2# J55 8 rd : burton Lite w s Class C wi	nd ST&C with th
2/3/85 Spudded 1 cemented 2/12/85 Drilled t casing. 1/4# flos 2% CaCl. Press plu	7½" hole at 11:0 13-3/8" casing. o 3700', Ran 89 Set and cemented eal and 15# salt Circulated 30's g to 1500#, held	oo a.m. 2/3 See previous (3701 at 3700 to per sack sacks to said 0K.	3/85 and drilious report73') 8-5/8" 2 with 1300 sad	led to 350 24# and 33 cks Hallil 300 sacks	O' and ran an 2# J55 8 rd : burton Lite w s Class C wi	nd ST&C with th
2/3/85 Spudded 1 cemented 2/12/85 Drilled t casing. 1/4# flos 2% CaCl. Press plu	7½" hole at 11:0 13-3/8" casing. o 3700', Ran 89 Set and cemented eal and 15# salt Circulated 30's g to 1500#, held	oo a.m. 2/3 See previous (3701 at 3700 to per sack sacks to said 0K.	3/85 and drilious report73') 8-5/8" 2 with 1300 sad	led to 350 24# and 33 cks Hallil 300 sacks	O' and ran an 2# J55 8 rd : burton Lite w s Class C wi	nd ST&C with th
2/3/85 Spudded 1 cemented 2/12/85 Drilled t casing. 1/4# flos 2% CaCl. Press plu	7½" hole at 11:0 13-3/8" casing. o 3700', Ran 89 Set and cemented eal and 15# salt Circulated 30's g to 1500#, held	oo a.m. 2/3 See previous (3701 at 3700 to per sack sacks to said 0K.	3/85 and drilious report73') 8-5/8" 2 with 1300 sad	led to 350 24# and 33 cks Hallil 300 sacks	O' and ran an 2# J55 8 rd : burton Lite w s Class C wi	nd ST&C with th
2/3/85 Spudded 1 cemented 2/12/85 Drilled t casing. 1/4# flos 2% CaCl. Press plu	7½" hole at 11:0 13-3/8" casing. o 3700', Ran 89 Set and cemented eal and 15# salt Circulated 30's g to 1500#, held	oo a.m. 2/3 See previous (3701 at 3700 to per sack sacks to said 0K.	3/85 and drilious report73') 8-5/8" 2 with 1300 sad	led to 350 24# and 33 cks Hallil 300 sacks	O' and ran an 2# J55 8 rd : burton Lite w s Class C wi	nd ST&C with th
2/3/85 Spudded 1 cemented 2/12/85 Drilled t casing. 1/4# flos 2% CaCl. Press plu	7½" hole at 11:0 13-3/8" casing. o 3700', Ran 89 Set and cemented eal and 15# salt Circulated 30's g to 1500#, held	oo a.m. 2/3 See previous (3701 at 3700 to per sack sacks to said 0K.	3/85 and drilious report73') 8-5/8" 2 with 1300 sad	led to 350 24# and 33 cks Hallil 300 sacks	O' and ran an 2# J55 8 rd : burton Lite w s Class C wi	nd ST&C with th
2/3/85 Spudded 1 cemented 2/12/85 Drilled t casing. 1/4# flos 2% CaCl. Press plu	7½" hole at 11:0 13-3/8" casing. o 3700', Ran 89 Set and cemented eal and 15# salt Circulated 30's g to 1500#, held	oo a.m. 2/3 See previous (3701 at 3700 to per sack sacks to said 0K.	3/85 and drilious report73') 8-5/8" 2 with 1300 sad	led to 350 24# and 33 cks Hallil 300 sacks	O' and ran an 2# J55 8 rd : burton Lite w s Class C wi	nd ST&C with th
2/3/85 Spudded I cemented 2/12/85 Drilled t casing. 1/4# flos 2% CaCl. Press plu	7½" hole at 11:0 13-3/8" casing. o 3700', Ran 89 Set and cemented eal and 15# salt Circulated 30's g to 1500#, held	oo a.m. 2/3 See previous (3701 at 3700 to per sack sacks to said 0K.	3/85 and drilious report73') 8-5/8" 2 with 1300 sad	led to 350 24# and 33 cks Hallil 300 sacks	O' and ran an 2# J55 8 rd : burton Lite w s Class C wi	nd ST&C with th
2/3/85 Spudded 1 cemented 2/12/85 Drilled t casing. 1/4# flos 2% CaCl. Press plu	7½" hole at 11:0 13-3/8" casing. o 3700', Ran 89 Set and cemented eal and 15# salt Circulated 30's g to 1500#, held	oo a.m. 2/3 See previous (3701 at 3700 to per sack sacks to said 0K.	3/85 and drilious report73') 8-5/8" 2 with 1300 sad	led to 350 24# and 33 cks Hallil 300 sacks	O' and ran an 2# J55 8 rd : burton Lite w s Class C wi	nd ST&C with th
2/3/85 Spudded I cemented 2/12/85 Drilled t casing. 1/4# flos 2% CaCl. Press plu Witnessed	7½" hole at 11:0 13-3/8" casing. o 3700', Ran 89 Set and cemented eal and 15# salt Circulated 30 s g to 1500#, held by Walter Cox w	jts (3701 i at 3700't per sack to sid OK.	3/85 and drilious report. .73') 8-5/8" 2 with 1300 sac followed by urface. Plug	led to 350 24# and 36 cks Hallil 300 sacks down @ 9	O' and ran and 2# J55 8 rd starton Lite vis Class C win: 45 a.m. 2/1	ond ST&C With th 2/85.
2/3/85 Spudded I cemented 2/12/85 Drilled t casing. 1/4# flos 2% CaCl. Press plu Witnessed	7½" hole at 11:0 13-3/8" casing. o 3700', Ran 89 Set and cemented eal and 15# salt Circulated 30 s g to 1500#, held by Walter Cox w	jts (3701 i at 3700't per sack to sid OK.	3/85 and drilious report73') 8-5/8" 2 with 1300 sad	led to 350 24# and 36 cks Hallil 300 sacks down @ 9	O' and ran and 2# J55 8 rd starton Lite vis Class C win: 45 a.m. 2/1	nd ST&C with th
2/3/85 Spudded I cemented 2/12/85 Drilled t casing. 1/4# flos. 2% CaCl. Press plu Witnessed	7½" hole at 11:0 13-3/8" casing. o 3700', Ran 89 Set and cemented eal and 15# salt Circulated 30's g to 1500#, held by Walter Cox w	jts (3701 i at 3700't per sack to sid OK.	3/85 and drilious report. .73') 8-5/8" 2 with 1300 sac followed by urface. Plug	led to 350 24# and 36 cks Hallil 300 sacks down @ 9	2# J55 8 rd : burton Lite vs Class C wi :45 a.m. 2/1	ond ST&C With th 2/85.
2/3/85 Spudded I cemented 2/12/85 Drilled t casing. 1/4# flos. 2% CaCl. Press plu Witnessed	7½" hole at 11:0 13-3/8" casing. o 3700', Ran 89 Set and cemented eal and 15# salt Circulated 30 s g to 1500#, held by Walter Cox w	jts (3701 i at 3700't per sack to sid OK.	3/85 and drilious report. .73') 8-5/8" 2 with 1300 sac followed by urface. Plug	led to 350 24# and 36 cks Hallil 300 sacks down @ 9	2# J55 8 rd : burton Lite vs Class C wi :45 a.m. 2/1	ond ST&C With th 2/85.

*See Instructions on Reverse Side

RECEIVED

FEB 18 1985

HOME OFFICE