

API No. 30-025-29281

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil well ☐ gas well ☐ other Dry Hole
2. NAME OF OPERATOR
Sun Exploration & Production Co.
3. ADDRESS OF OPERATOR
P.O. Box 1861, Midland, Texas 79702
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)
AT SURFACE: 1980' FSL & 660' FEL of
AT TOP PROD. INTERVAL: Sec. 29-18S-34E
AT TOTAL DEPTH: Unit Letter I

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
CHANGE ZONES ☐
ABANDON* ☒
(other) ☐

☐
☐
☐
☐
☐
☐
☐
☐
☐

5. LEASE
NM-12277
6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME
Pennzoil "A" Federal
9. WELL NO.
1
10. FIELD OR WILDCAT NAME
Und. Bone Spring (EK East)
11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA
Sec. 29-18S-34E
12. COUNTY OR PARISH Lea 13. STATE NM
14. API NO.

15. ELEVATIONS (SHOW DF, KDB, AND WD)
3970 GR

(NOTE: Report results of multiple completion or zone change on Form 9-330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

1. TIH w/DCS LD DCS. TIH w/DP OE to 9650'
2. Spot a 45 sks CL H cmt plug from 9650 to 9500'.
3. Spot a 45 sks CL H cmt plug from 7925 to 7775.
4. Spot a 45 sks CL H cmt plug from 6825 - 6675.
5. Spot a 45 sks CL H cmt plug from 5560 - 5410.
6. Spot a 35 sks CL H cmt plug from 4614 - 4500.
7. Spot 35 sks CL H cmt plug from 3750-3650.
8. Spot 35 sks CL H cmt plug from 3200-3100.
9. Spot 35 sks CL H cmt plug from 1945-1845.
10. Spot 35 sks CL H cmt plug from 400-300.
11. Spot 20 sks CL H surf. plug.
12. Cut off wellhead 5' BGL. Weld on steel plate & dry hole marker.

Subsurface Safety Valve: Manu. and Type _____ Set @ _____ Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED Delma Reyes TITLE Sr. Accting. Asst DATE 9/13/85

(This space for Federal or State office use)

APPROVED BY [Signature] TITLE _____ DATE 11-1-85
CONDITIONS OF APPROVAL, IF ANY: _____

Instructions

General: This form is designed for submitting proposals to perform certain well operations, and reports of such operations when completed, as indicated, on Federal and Indian lands pursuant to applicable Federal law and regulations, and, if approved or accepted by any State, on all lands in such State, pursuant to applicable State law and regulations. Any necessary special instructions concerning the use of this form and the number of copies to be submitted, particularly with regard to local, area, or regional procedures and practices, either are shown below or will be issued by, or may be obtained from, the local Federal and/or State office.

Item 4: If there are no applicable State requirements, locations on Federal or Indian land should be described in accordance with Federal requirements. Consult local State or Federal office for specific instructions.

Item 17: Proposals to abandon a well and subsequent reports of abandonment should include such special information as is required by local Federal and/or State offices. In addition, such proposals and reports should include reasons for the abandonment; data on any former or present productive zones, or other zones with present significant fluid contents not sealed off by cement or otherwise; depths (top and bottom) and method of placement of cement plugs; mud or other material placed below, between and above plugs; amount, size, method of parting of any casing, liner or tubing pulled and the depth to top of any left in the hole; method of closing top of well; and date well site conditioned for final inspection looking to approval of the abandonment.

GPO : 1981 0 - 347-166

RECEIVED
NOV 4 - 1985
FEDERAL
RODAS OFFICE