

- 4) FRAC DELAWARE DOWN 5-1/2" CSG W/ 8000 GAL REFINED GUAR, 14000# 20/40 BRADY SD & 3200# 20/40 CRCS @ 30 BPM AS FOLLOWS (MAX PRESS 3800 PSI, EXPECTED TREATING PRESS 2000 PSI):
  - A) PUMP 2500 GAL PAD
  - B) PUMP 650 GAL W/ 1 PPG 20/40 BRADY SD
  - C) PUMP 800 GAL W/ 2 PPG 20/40 BRADY SD
  - D) PUMP 1250 GAL W/ 3 PPG 20/40 BRADY SD
  - E) PUMP 2000 GAL W/ 4 PPG 20/40 BRADY SD
  - F) PUMP 800 GAL W/ 4 PPG 20/40 CRCS
  - G) FLUSH TO TOP PERF W/ 2% KCL WTR
- 5) FLOW WELL 1 HR @ 15 BPH RATE. SI WELL OVERNITE.
- 6) TIH W/ MA, PN, SN, 10 JTS 2-7/8" TBG & 5-1/2" TAC ON 2-7/8" PROD TBG TO 5400'. SET TAC IN 18 PTS TENSION & NU WH. RIH W/ 2" INSERT PUMP W/ GAS ANCHOR ON 3000' - 3/4" D RODS & 2250' - 7/8" D RODS. HANG WELL ON. RR.