Form 3160–5
(November 1983)
(Formerly 9–331)

UNITED TATES
DEPARTMENT O₁ THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE
(Other Instructions on
verse side)

Form approved.
Budget Bureau No. 1004–0
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL

NM-50920

SUNDRY NOTICES AND REPORTS ON WELLS
(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

1.
OIL WELL [X]   GAS WELL [ ]   OTHER

7. UNIT AGREEMENT NAME

2. NAME OF OPERATOR

Mewbourne Oil Company

8. FARM OR LEASE NAME

Federal "I"

3. ADDRESS OF OPERATOR

P. O. Box 7698, Tyler, Texas 75711

9. WELL NO.

1

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface

1980' FSL & 1980' FEL

10. FIELD AND POOL, OR WILDCAT

Reeves-Penn

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

14-18S-35E

14. PERMIT NO.

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

12. COUNTY OR PARISH | 13. STATE

Lea | *N.M.*

16.

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF [ ]	PULL OR ALTER CASING [ ]	WATER SHUT-OFF [ ]	REPAIRING WELL [ ]
FRACTURE TREAT [ ]	MULTIPLE COMPLETE [ ]	FRACTURE TREATMENT [ ]	ALTERING CASING [ ]
SHOOT OR ACIDIZE [ ]	ABANDON* [ ]	SHOOTING OR ACIDIZING [ ]	ABANDONMENT* [ ]
REPAIR WELL [ ]	CHANGE PLANS [ ]	(Other) *Spud & set surface casing*	[X]
(Other)			

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

*8/22/85 - Spud well at 4:00 P.M. 8/21/85. Ran 1 collar, insert float,
3 centralizers, 10 joints 13-3/8" 54.5# MR. set at 418'. Halliburton
cemented with 200 sacks Class HLC with 5.3# soft, 14/# flocele, and
200 sacks Class C with 2% CaCl. PD to 378.26' at 2:00 A.M. Circulated
90 sacks.*

18. I hereby certify that the foregoing is true and correct

SIGNED *[signature]*   TITLE *Exploration Secretary*   DATE *August 23, 1985*

(This space for Federal or State office use)

ACCEPTED FOR RECORD

APPROVED BY _____   TITLE _____   DATE _____
CONDITIONS OF APPROVAL, IF ANY:

AUG 27 1985

See Instructions on Reverse Side

CARLSBAD, NEW MEXICO