

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 30 through 34 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico

Northwestern New Mexico

T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn 12,211'	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka 12,532'	T. Pictured Cliffs	T. Penn. "D"
T. Yates	T. Miss (Chester) 13,609	T. Cliff House	T. Leadville
T. 7 Rivers	T. Devonian	T. Menefee	T. Madison
T. Queen	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres	T. Simpson	T. Gallup	T. Ignacio Qtzte
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinebry	T. Gr. Wash	T. Morrison	T.
T. Tubb	T. Granite	T. Todilto	T.
T. Drinkard	T. Delaware Sand 6160'	T. Entrada	T.
T. Abo	T. Bone Springs 7653'	T. Wingate	T.
T. Wolfcamp 10,290'	T. Morrow 12,909'	T. Chinle	T.
T. Penn.	T. Middle Morrow 13,297'	T. Permian	T.
T. Cisco (Bough C)	T. Lower Morrow 13,476'	T. Penn. "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to.....	No. 4, from.....to.....
No. 2, from.....to.....	No. 5, from.....to.....
No. 3, from.....to.....	No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....	feet.....
No. 2, from.....to.....	feet.....
No. 3, from.....to.....	feet.....
No. 4, from.....to.....	feet.....

FORMATION RECORD (Attach additional sheets if necessary)

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
6160'	7653'	1493	Delaware Sds.				
7653	8935	1282	Bone Spring				
8935	8992	57	1 st Bone Spring Sd.				
8992	9572	580	2 nd Bone Spring Carbonate				
9572	10054	482	2 nd Bone Spring Sand				
10054	10178	124	3 rd Bone Spring Carbonate				
10178	10290	112	3 rd Bone Spring Sand				
10290	12211	1921	Wolfcamp				
12211	12532	321	Strawn				
12532	12909	377	Atoka				
12909	13297	388	Morrow				
13297	13476	179	M. Morrow				
13476	13609	133	L. Morrow				
TD							