

- 3) RU D-S. FRAC DELAWARE DOWN 5-1/2" CSG @ 15 BPM W/ 4100 GAL REFINED GUAR, 7500# 20/40 BRADY SAND & 1600# 20/40 CRCS AS FOLLOWS (MAX PRESS 3800 PSI, EXPECTED TREATING PRESS 2000 PSI):
 - A) PUMP 1200 GAL PAD
 - B) PUMP 350 GAL W/ 1 PPG 20/40 BRADY SD
 - C) PUMP 400 GAL W/ 2 PPG 20/40 BRADY SD
 - D) PUMP 650 GAL W/ 3 PPG 20/40 BRADY SD
 - E) PUMP 1100 GAL W/ 4 PPG 20/40 BRADY SD
 - F) PUMP 400 GAL W/ 4 PPG 20/40 CRCS
 - G) FLUSH TO TOP PERF W/ ±128 BBL 2% KCL WTR
- 4) FLOW WELL 1 HR @ 15 BPH RATE. SI WELL OVERNITE.
- 5) TIH W/ MA, PN, SN, 10 JTS 2-7/8" TBG & TAC ON 2-7/8" TBG TO 5350'. SET TAC IN 18 PTS TENSION & NU WH. RIH W/ 2" INSERT PUMP W/ GAS ANCHOR ON 2950' - 3/4" KD RODS & 2300' - 7/8" KD RODS. HANG WELL ON. RR.