

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

EXEMPT FROM FEDERAL ACQUISITION
OTHER INSTRUCTIONS

DESIGNATION AND SERIAL NO.
NM-26884-A
INDIAN, RESERVE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		7. UNIT ASSIGNMENT NAME	
2. NAME OF OPERATOR Cavalcade Oil Corporation		8. FARM OR LEASE NAME Conoco Federal	
3. ADDRESS OF OPERATOR P.O. Box 16187, Lubbock, TX 79490		9. WELL NO. 1	
4. LOCATION OF WELL Report location clearly and in accordance with any State requirements. See also space 17 below. At surface 660' FNL & 660' FEL		10. FIELD AND POOL, OR WILDCAT Wildcat	
14. PERMIT NO. API-30-025-29483		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 8, T18S, R33E	
15. ELEVATIONS (Show whether OF, ST, OR PL.) 3984.0 GR		12. COUNTY OR PARISH Lea	
		13. STATE NM	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETE ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON* ☐	SHOOTING OR ACIDIZING ☐	ABANDONMENT* ☒
REPAIR WELL ☐	CHANGE PLANE ☐	(Other) ☐	

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

1/07/86 Plug and abandon well as follows:

Plug #1: 3450' to 3250', 55 sx Class "C" cement w/2% CaCl₂. Waited 4 hrs and tagged top of plug #1 @ 3231', witnessed by Walter Cox, BLM.

Plug #2: 1600' to 1500', 26 sx Class "C" cement w/2% CaCl₂.

Plug #3: 480' to 380', 26 sx Class "C" cement w/2% CaCl₂.

Plug #4: 50' to surface, 15 sx Class "C" cement w/2% CaCl₂.

Dry hole marker was installed 5' above ground level. Prior to setting plugs the hole was displaced with drilling mud 2500# gel/100 BBLs water.

Above procedure was approved by Mr. Pitchke and witnessed Mr. Cox, BLM.

I hereby certify that the foregoing is true and correct

SIGNED Michael G. Mooney TITLE Drilling & Prod. Manager DATE 1/15/86
This space for Federal or State office use

APPROVED BY _____ TITLE _____ DATE 8-6-86
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side