

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE
Obey instructions
Reverse side

RECEIVED AUGUST 11 1985
LEASE DESIGNATION AND SERIAL NO.
NM-26884-A
NAME OF INDIAN, ALGONQUIN OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR Cavalcade Oil Corporation		8. FARM OR LEASE NAME Conoco Federal	
3. ADDRESS OF OPERATOR P. O. Box 16187, Lubbock, TX 79490		9. WELL NO. 1	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 660' FNL & 660' FEL		10. FIELD AND POOL, OR WILDCAT Wildcat	
		11. SEC., T., S., R., OR BLM. AND SUBVY OR AREA Sec. 8, T18S, R33E	
14. PERMIT NO. API 30-025-29483	15. ELEVATIONS (Show whether OF, ST, GR, etc.) 3984.0 GR	12. COUNTY OR PARISH Lea	13. STATE NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF ☐	PULL OR ALTER CASING ☐	WATER SHUT-OFF ☐	REPAIRING WELL ☐
FRACTURE TREAT ☐	MULTIPLE COMPLETS ☐	FRACTURE TREATMENT ☐	ALTERING CASING ☐
SHOOT OR ACIDIZE ☐	ABANDON ☒	SHOOTING OR ACIDIZING ☐	ABANDONMENT ☐
REPAIR WELL ☐	CHANGE PLANS ☐	(Other) ☐	

Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Cavalcade Oil Corporation proposes to plug and abandon the Conoco Federal #1 well. The following plugging procedure was recommended by Mr. Bob Pitchke of The BLM. Set plug #1 across Yates perforations (50' above and 50' below) from 3250' - 3450'. Plug #2 from 1500'-1600' to cover top of salt. Plug #3 from 380'-480' (across surface casing shoe). Plug #4 - 50' surface plug. Plug #1 will be tagged after 12 hours to be sure it did not fall. Drilling Mud will be placed in pipe between plugs.

I hereby certify that the foregoing is true and correct

SIGNED [Signature]

TITLE Drilg. & Prod. Manager

DATE 1/3/86

(This space for Federal or State office use)

APPROVED BY _____
CONDITIONS OF APPROVAL, IF ANY:

TITLE _____

DATE 1-8-86

*See Instructions on Reverse Side

RECEIVED

JAN 13 1986

RECEIVED