	Form approved.
Form 3.50-5- UNI) STATES SUBMIT IN TRIPE E- (November 1983) (Other instructions of THE INTERIOR verse side)	Budget Bureau No. 1004-0135 Expires August 31, 1985 5. LEASE DESIGNATION AND BERIAL NO
BUREAU OF LAND MANAGEMENT RECEIVED	NM-04591
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use "APPLICATION FOR PERMIT—" for such proposals.)	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
OIL GAS WELL OTHER	7. UNIT AGREEMENT NAME
2 Sun Exproration & Production Co.	8. FARM OF LEASE NAME "D" Fed. Mescalero Ridge "D" Fed.
P.O. Box 1861, Midland, Texas 79702	9. WELL NO.
4. Location of Well (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surfactinit Letter B, 330' FNL & 2000' FEL	Mescalero Escarpe Bone 11. sec., T., E., M., OR BLK. AND SURVEY OR AREA SOC. 14. T. 10. S. D. 22. F.
14. PERMIT NO. 15. ELEVATION (Show whether DP, RT, GR, etc.)	Sec. 14, T-18-S, R-33-E
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Ot	ther Data
	NT REPORT OF:
TEST WATER SHUT-OFF PULL OR ALTER CASING WATER SHUT-OFF PRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL (104 Do C CHANGE PANSA) WATER SHUT-OFF PRACTURE TREATMENT SHOOTING OR ACIDIZING (Other)	ALTEBING CASING ABANDONMENT®
(IST Bone Spring Sand) (Note: Report results o	f multiple completion on Well ion Report and Log form.) actuding estimated date of starting any depths for all markers and zones perti-
1. HOT OIL CSG 2 DAYS PRIOR TO MIRU, USING 75 BBLS LSE OIL. PU	T WELL ON HAND.
2. MIRU PU. POH W/ 86 TAPER 'KD' ROD STRING & 2-1/2"x1-1/2"x24 ND WH. NU BOP. RLSE TAC AND POH W/ 2-7/8", 6.5#, J-55 PROD	' ROD PUMP. TBG.
NOTE: TOP ±4000' OF TBG STRING MAY NEED TO BE LAYED DOW DUE TO ESCESSIVE PARAFFIN BUILD-UP.	N AND STEAMED OUT
3. MIRU NL McCULLOUGH. RIH W/ WL SET, 5-1/2", 17# RBP. SET RB GR/CD-CNL DATED 01/15/86. PERF BONE SPRING SAND SET III 835 40 HOLES USING 4" OD, 22.5 GC, .53" EH CSG GUN, 120° PHASE V DATED 01/15/86.	7-83964, 1 JSPF, TOTAL
4. RIH W/ 5-1/2", 17# RDG (SMALL BORE) PKR, RETRIEVING HEAD & SITO ±8400 PSI TESTING TBG TO 5000 PSI. MIRU BJ-TITAN. SPOT W/ ADDITIVES* FROM 8400 TO 8314'. RAISE & SET PKR @ ±8250' LOAD BACKSIDE. ND BOP. NU BONNET & MASTER VALVE. TRAP 1500 SPRING SAND SET III 8357-8396' USING 4000 GALS 15% NEFE HCL STAGE @ ±5 BPM. DIVERT ACID USING 60 1.1 SP GR, 7/8" RCN BS CLUSTERS OF 5 SPACED EVENLY THRUOUT ACID. MAX TREATING PRESE WHTP 4000 PSI. FLUSH TO BTM PERF USING 2150 GALS NE 2% KCL	2 BBLS 15% NEFE HCL W/ 22 PTS COMPRESSION. O PSI CP. ACDZ BONE W/ ADDITIVES* IN ONE . DROP BALLS IN S 5500 PSI. ANTICIPATED
18. I hereby certify that the foregoing is true and correct SIGNED (1971) TOWNED ASSOCIATE ACCOUNTANT	8/3/88
SIGNED (TITLE ASSOCIATE ACCOUNTANT (This space for Federal or State office use)	DATE 0/ 5/ 00
APPROVED BY CHIEF, No. 128/12/2018/07/3 CONDITIONS OF APPROVAL, IF ANY:	DATE 8-16.55