

- 7/30/86 Test csg & RBP @ 8764 to 1500 - OK, GO W.L. perf B.S. set II 8710-8746
2 JSPF 73 holes w 4" O.D. csg gun, 23 G.C. by Gearhart RIH w BJ Titan
PFT on 2-7/8 tbg 8710, break circ & round trip PFT tool 8710-46 in circ
MODE w treated 2% KCL wtr, 2-1/2 BPM circ rate, spot 500 gals 20% NEFEHCL
to PFT tool, close csg valve & displaced acid into perfs 8710-46 while
round tripping PFT in inject MODE, 1-1/2 BPM & 1000 PSI cp, ISIP 910, 10
min vac
- 7/31/86 Finish RIH w/5-1/2 RDG on 2-7/8 tbg set pkr 8588
- 8/1/86 B.J. TITAN trap 500 on csg, B.J. acdz Bone Springs set II 8710-8746
w/2000 gal 20% NEFEHCL, flush w/treated 2% KCL
- 8/5/86 Rel pkr 1 wr thru perfs tag & latch RBP POH w/pkr & RBP TIH w/2-7/8"
prod. tbg & pumping setup TS 8823 SN 8788' 5-1/2" Guib. TAC at 8613'
set w/15,000# tension ND BOP NU wellhead RIH w/2-1/2x1-1/2x24' pump
on 86 rod string Start well pumping
- 8/13/86 24 hrs P, 92 B0, 5 BW, 125 MCF, GOR 1352/1, GR 40.4 API Corr @ 60
8x168x1-1/2 FL on SN @ 8788

RECEIVED
AUG 20 1986
O.C.
HOBBS OFFICE