1-26-86

UNITED STAPES 1.EXICO 8824D DEPARTMENT OF THE TRYERIOR **GEOLOGICAL SURVEY** SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)

DEPARTMENT OF THE INTERIOR GEOLOGICAL SURVEY	NM - 14000 6. IF INDIAN, ALLOTTEE OR TRIBE NAME.
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331—C for such proposals.) 1. oil gas well other 2. NAME OF OPERATOR TXO Production Corp. 3. ADDRESS OF OPERATOR 900 Wilco Bldg. Midland, Texas 4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.) AT SURFACE: 2310 FNL & 2310 FEL AT TOP PROD. INTERVAL: AT TOTAL DEPTH:	7. UNIT AGREEMENT NAME 8. FARM OR LEASE NAME Burleson Federal 9. WELL NO. 3 10. FIELD OR WILDCAT NAME Querecho Plains (Upper Bone Spring: 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 26, T-18-S, R-32-E 12. COUNTY OR PARISH 13. STATE Lea New Mexico 14. API NO.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: TEST WATER SHUT-OFF	15. ELEVATIONS (SHOW DF, KDB, AND WD) 3752 GL & 3763 KB (NOTE: Report results of multiple completion or zone change on Form 9–330.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Spud 17-1/2" hole. Ran 11-3/4" casing, set @ 350'.

SIGNED LUU	(This space for Federal or State office use)	4 - 2 - 86
18. I hereby certify th	ve: Manu. and Type	•
Subsurface Safety Val	•	
2-13-86 2-14-86	Ran 4-1/2" casing. Set @ 8729'. Ce ξ 100sx 50/50 poz "H".	ement w/1600sx lite
1-30-86 thru	Drilling 7-7/8" hole.	
1-29-86	Ran 8-5/8" casing. Set @ 2804'. & 500sx "C".	Cement w/1500sx lite
1 - 2 7 - 8 6 1 - 2 8 - 8 6	Set w/485sx "C". Ran 4 centralize Drilling 11" hole.	ers. Circulated cement.

ACCEPTED FOR RECORD

*See Instructions ArD Reverse Sid 986