HNITED STATES

DEPARTMENT OF THE INTERIOR	5. LEASE LC-063645
GEOLOGICAL SURVEY	6. IF INDIAN, ALLOTTEE OR TRIBE NAME
SUNDRY NOTICES AND REPORTS ON WELLS (Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9–331–C for such proposals.)	7. UNIT AGREEMENT NAME
reservoir, use ruthin 3-331-C for Such proposats.)	8. FARM OR LEASE NAME
1. oil XX gas	Mescalero Ridge Federal
	9. WELL NO.
2. NAME OF OPERATOR Sun Exploration and Production Co.	2
3. ADDRESS OF OPERATOR	10. FIELD OR WILDCAT NAME Mescalero Escarpe Bone Spring
P.O. Box 1861 Midland, Texas 79702	11. SEC., T., R., M., OR BLK. AND SURVEY OR
4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17	AREA
helow)	Sec. 13, T-18-S, R-33-E
AT SURFACE: 1700' FNL & 1700' FEL	12. COUNTY OR PARISH 13. STATE NM
AT TOP PROD. INTERVAL: AT TOTAL DEPTH: finit I to G	Lea NM
OHITE ECH. U	14 . API NQ.
16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE,	30-025-29437
REPORT, OR OTHER DATA	15. ELEVATIONS (SHOW DF, KDB, AND WD) 4006.8' GR
REQUEST FOR APPROVAL TO: SUBSEQUENT REPORT OF: FRACTURE TREAT SHOOT OR ACIDIZE REPAIR WELL PULL OR ALTER CASING MULTIPLE COMPLETE CHANGE ZONES (other) CASSING Data SUBSEQUENT REPORT OF: SUBSECUENT REPORT OF: SUBSECUEN	(NOTE: Report results of multiple completion or zone change on Form 9–330.)
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)* 11-5-85	
Ran & Set 79 Jts 8 5/8" Csg. Cs 3241, FC 3201, Cir. hole, BJ Cmt. w/600 Sxs BJ Lite +10% Salt, +1/4#/SK Cellophane, Tail in w/300 Sxs "C". Circ. 100 Sxs Cmt. to Surf. Cur off Tested BOP and Csg. to 2100 PSI for 1/2 Hr. Tested Pipe Rams to 2100 O.K. 11-30-85 Ran & Cmt. 217 Jts, 5 1/2" Csg. CS 9300, FC 9232, Stage Collar 6979, BJ-Titan	
precede Cmt. w/500 Gals of Mud Flush. Cmt. 1st stage , 600 Sxs Class "C" 50/50 Poz A +2% Gel. + .3% FL-19 Open Stage Collar Circ. thur collar 4 1/4 Hrs. Circ. 168 Sx Cmt. off stage Collar. Cmt. 2nd Stage w/800 Sxs BJ Lite + 10% Salt tail in w/50 Sxs Class "C" Neat Close Stage Collar, Set Slips, Cut off 5 1/2" Csg. Ran Temp Sur. TOC 500'	
Subsurface Safety Valve: Manu and Type	Set @ Ft.
18. I hereby certify that the foregoing is true and correct	
SIGNED DIFF TITLE ASSOCIATE ACCOUNTANT 1-6-86	
(This space for Federal or State office use)	

APPROVED AV. CEPTED FOR RECORD CONDITIONS OF APPROVAL, IF ANY:

JAN 7 1980