

P. O.

HOBBS, NEW MEXICO

Form Approved  
Budget Bureau No. 47-R14.1

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
GEOLOGICAL SURVEY

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir. Use Form 9-331-C for such proposals.)

1. oil ☒ gas ☐  
well well other

2. NAME OF OPERATOR  
Metex Pipe & Supply

3. ADDRESS OF OPERATOR  
P. O. Box 1037 Artesia, N. M. 88210

4. LOCATION OF WELL (REPORT LOCATION CLEARLY. See space 17 below.)  
AT SURFACE: 2310' FSL & 990' FSL  
AT TOP PROD. INTERVAL:  
AT TOTAL DEPTH:

16. CHECK APPROPRIATE BOX TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

REQUEST FOR APPROVAL TO:	SUBSEQUENT REPORT ON:
TEST WATER SHUT-OFF	
FRACTURE TREAT	
SHOOT OR ACIDIZE	
REPAIR WELL	
PULL OR ALTER CASING	
MULTIPLE COMPLETE	
CHANGE ZONES	
ABANDON*	
(other) Spud & Cement Surface casing	X

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)\*

Spud well with LaRue Drilling Rig #2 at 4:45 PM 4-30-86. Notify BLN via telephone. Drill 12 1/4" hole to 375' KB and set 9 jts, 374' 8 5/8" 24" J-55 casing. Shoe at 372' KB. Pumped 250 sx Paliburton Class "C" cement with 2" CaCl and circulated 25 sx. to pit. Plug down at 11:15 PM 4-30-86. WOC 18 hours and drill out 2' past shoe and tested BOP to 500 P.S.I. Pressure held for 30 Minutes. Presently drilling 7 7/8" hole with full returns.

ACCEPTED FOR RECORD

*Handwritten signature*  
MAY 5 1986

Subsurface Safety Valve: Manu. and Type CARLSBAD, NEW MEXICO

Set @ . . . . . Ft.

18. I hereby certify that the foregoing is true and correct

SIGNED *Martin B. Murey* TITLE *Asst. Metex Pipe & Supply*

DATE 5-1-86

APPROVED BY  
CONDITIONS OF APPROVAL, IF ANY.

TITLE

DATE