Form 3160-5	UN. D STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT		SUBMIT IN TRIPL. 1TE* (Other instructions on re- verse side)	Form approved. Budget Bureaus No. 1004-0135 Expires August 31, 1985		
(November 1983) (Formerly 9-331)				5. LEASE DESIGNATION AND	5. LEASE DESIGNATION AND SERVAL NO.	
•				NMNM84603X 6 FINDWA ALIOTTEE OR TRIBE NAME		
St	JNDRY NOTICES AND RE	en or plug back to	a different reservoir.			
(Do not use t	Use "APPLICATION FOR PERMIT"	for such proposal	6.)	7.UNIT AGREEMENT NAME		
1				CENT. CORBIN C	DUEEN UT.	
OIL GAS OTHER WATER INJECTION				& FARM OR LEASE NAME		
2 NAME OF OPERATOR	OXY USA INC.				_	
3. ADDRESS OF OPERATO		TV 70710		a WELNO.		
P.O. BOX 30230 MINDS 1145, 174 1011					10. FIELD AND POOL, OR WILDCAT	
4. LOCATION OF WELL (Fla See also space 17 below	port location clearly and in accordance with any St	CORBIN QUEEN, CENTRAL				
At surface	and c			11. SEC, T., R, M., OR BLK SURMEY OR AREA		
1980 FNL 560	FWL Sec 3 T18S R33E				225	
				Sec 3 T18S R	133E	
14. PERMIT NO.	15. ELEVATIONS (Showw	heter DF, RT, GR, etc.)		LEA	NM	
30025297980	00801			1		
16.	Check Appropriate Box To In-	dicate Nature	of Notices, Report, o	SEQUENTREPORTOF:		
n Testwatershut			WATER SHUT-OFF FRACTURE TREATMENT	REPAIRING	CASING	
FRACTURETREAT	MULTIPLE COMPLETE ABANDON*	H	SHOOTING OR ACIDIZING	ABANDONI X	WENT'S	
SHOOT OR ACIDIZI REPAIRWELL	CHANGEPLANS		(Other) CONVERT TO	WATER INJECTION on multiple completion on	Well Caran	
	OSED OR COMPLETED OPERATIONS (Clear		OIntion or Doco	moletion Report and Log [0	m.) // / / / / /	
nent to this wo) - 4260'	PERFS - 4211	'-4215 <i>'</i>		
W/ RTT PERFS	PU, POOH W/ RODS, PUMP TS & SET @ 4124', TES (4211-4215') W/ 2000 RIH W/ GUIBERSON C- , NUWH, CIRC W/ PKR READY FOR INJECTION.	GAL 15%	NEFE HCL ACID 2-3/8 FG TBG ST CSG TQ 13 500	, SWAB BACK I & SET @ 411 HELD OK, F	OAD.	
18. Thereby certify the	at the foregoing is true and correct	TITLEPROI	DUCTION ACCOUNTA		44/9/	
(This space for Fe	oderal or State office use)					
•	BY	TITLE		DATE		
	S OF APPROVAL, IF ANY:					

*See Instructions on Reverse Side

