

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	
LG 5682	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - 1" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Yates Petroleum Corporation		8. Farm or Lease Name Shooting Star AEA State
3. Address of Operator 105 South 4th St., Artesia, NM 88210		9. Well No. 1
4. Location of Well UNIT LETTER <u>J</u> <u>1650</u> FEET FROM THE <u>South</u> LINE AND <u>2310</u> FEET FROM THE <u>East</u> LINE, SECTION <u>11</u> TOWNSHIP <u>18S</u> RANGE <u>35E</u> NMPM.		10. Field and Pool, or Wildcat Reeves Bone Spring
15. Elevation (Show whether DF, RT, GR, etc.) 3891.1' GR		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input checked="" type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <u>Set Surface pipe</u> <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Paul Carre, Yates Petroleum Corporation, notified Ray Smith, NMOCD, Hobbs, NM 12-31-86 of spud.  
Spudded 8:00 PM 12-31-86. Ran 10 joints 13-3/8" 54.5# J-55 casing set 420'.  
1-Texas Pattern Notched guide shoe set 420', insert float set 485'. Cemented w/400 sx Class "C" with 2% CaCl2 (yield 1.32; weight 14.8). PD 2:45 PM 1-1-87.  
Bumped plug to 250 psi, released pressure and float held okay. Cement circulated 25 sacks. WOC. Drilled out 6:00 AM 1-2-87. WOC 15 hours and 15 minutes. NU and tested to 1000 psi for 30 minutes. OK. Reduced hole to 11". Drilled plug and resumed drilling.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jerry Sexton TITLE Production Supervisor DATE 1-2-87

ORIGINAL SIGNED BY JERRY SEXTON  
DISTRICT I SUPERVISOR

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE JAN 5 1987

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED  
JAN 5 1987  
OCD  
HOBBS OFFICE