

OIL CONSERVATION DIVISION

P. O. BOX 2088

SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

API No. 30-025-29815

5a. Indicate Type of Lease	
State ☒	Fee ☐
5. State Oil & Gas Lease No.	
B-2148	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒	GAS WELL ☐	OTHER ☐
Name of Operator		
Phillips Petroleum Company		
Address of Operator		
4001 Penbrook Street, Odessa, Texas 79762		
Location of Well		
UNIT LETTER <u>J</u> , <u>1805</u> FEET FROM THE <u>South</u> LINE AND <u>1980</u> FEET FROM		
THE <u>East</u> LINE, SECTION <u>21</u> TOWNSHIP <u>17-S</u> RANGE <u>33-E</u> NMPM.		

7. Unit Agreement Name
8. Farm or Lease Name
Leamex
9. Well No.
39
10. Field and Pool, or Wildcat
Maljamar-Grayburg/SA
12. County
Lea

15. Elevation (Show whether DF, RT, GR, etc.)

4167.8' GR (Unprepared)

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐
FULL OR ALTER CASING ☐	OTHER ☐

SUBSEQUENT REPORT OF:	
REMEDIAL WORK ☐	ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒	PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☒	OTHER ☐

Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

1-01-87: Spud 12 1/4" hole at 3:00 P.M.

1-02 thru

1-07-87: Drlg. TD'd 12 1/4" hole at 6:30 P.M. 1-03-87. Set 8 5/8" 24# K-55 ST&C csg at 1538'. Cemented with 1000 sx Class "C", 2% CaCl. Circ 250 sx cmt. Plug down at 2:20 P.M. WOC 18 hrs. NU BOP, tst'd to 1000 psi, ok.

1-08 thru

1-10-87: Drlg. TD'd 7-7/8" hole at 11:15 A.M. 1-10-87. Dresser Atlas ran DLL-MSFL-GR/Cal log, TD-2500'; CNL-LDT-GR-Cal, TD-2500; CNL-GR-Cal, 2500'-0. TD @4800'.

1-11-87: Set 5-1/2" 17# K-55 ST&C csg at 4805'. Cemented w/1200 sx Class "C", 10% DD, 9#/sx salt, tailed with 400 sx "C". 5#/sx salt. Circ 304 sx cmt. ND & Set slips. Rigged down. WOCU.

BOP EQUIP: Series 900, 3000#WP, double w/1 set pipe rams, 1 set blind rams, manually operated.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

W. J. Mueller

TITLE Engineering Supervisor, Reserv. DATE January 12, 1986

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

JAN 14 1987

RECEIVED
JAN 19 1987
DOD
HOBBS OFFICE

U.S. DEPARTMENT OF DEFENSE
OFFICE OF THE SECRETARY