

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPL
(Other instructions
verse side)

TE
re

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

| | | | |
|---|--|---|--|
| 1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/> | | 7. UNIT AGREEMENT NAME | |
| 2. NAME OF OPERATOR Mewbourne Oil Company | | 8. FARM OR LEASE NAME FEDERAL "F" | |
| 3. ADDRESS OF OPERATOR P. O. Box 7698, Tyler, Texas 75711 | | 9. WELL NO. 3 | |
| 4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 990' FWL & 1980' FSL | | 10. FIELD AND POOL, OR WILDCAT Querecho Plains - Upper Bone Springs | |
| 14. PERMIT NO. API #30-025-29828 | | 11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA 23-18S-32E | |
| 15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3764.2' GR | | 12. COUNTY OR PARISH Lea | |
| | | 13. STATE N.M. | |

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PULL OR ALTER CASING

MULTIPLE COMPLETE

ABANDON*

CHANGE PLANS

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other) Set Production String

REPAIRING WELL

ALTERING CASING

ABANDONMENT*

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

1-25-87 8570' TD. Lime & Sand. Rigged down. Ran casing as follows: FS, 42.10' shoe, FC, 12 centralizers,

| | | |
|----------------|---------------|----------|
| 168 jts 5-1/2" | 23# N-80 LT&C | 6673.56' |
| 33 jts 5-1/2" | 20# N-80 LT&C | 1285.67' |
| 15 jts 5-1/2" | 23# N-80 LT&C | 618.88' |
| Total | | 8578.11' |
| Set @ | | 8570' |

Western cemented with 1125 sxs PSL w/6% gel, 2# Hi Seal, .3% CF-2 & 250 sxs Class H w/.3% CF-14. Circ 50 sxs. SD cmt @ 9:15 PM. Pumped 2 bbl over disp & did not land plug. Checked floats - okay: Pumped another 2 bbls & did not land plug. SD disp. Set slips. Released rig @ 12 Midnight 1/24/87. Lift Press 2200#.

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Engr. Oprns. Sec.

DATE 1/28/87

(This space for Federal or State office use)

APPROVED BY

CONDITIONS OF APPROVAL, IF ANY:

TITLE

ACCEPTED FOR RECORD

*See Instructions on Reverse Side

FEB 02 1987

CARLSBAD, NEW MEXICO