

UNITED STATES  
DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIP.  
(Other instructions  
reverse side)

Form approved.  
Budget Bureau No. 1004-411  
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM-9218

38240 IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Mewbourne Oil Company

3. ADDRESS OF OPERATOR

P. O. Box 7698, Tyler, Texas 75711

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.\*  
See also space 17 below.)

At surface

990' FWL & 1980' FSL

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

FEDERAL "F"

9. WELL NO.

3

10. FIELD AND POOL OR WILDCAT

Querecho Plains -  
Upper Bone Springs

11. SEC., T., R., M., OR BLE. AND  
SURVEY OR AREA

23-18S-32E

14. PERMIT NO.

API #30-025-29828

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3764.2 GR

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON\*

REPAIR WELL

CHANGE PLANE

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT\*

(Other)

Set Intermediate Casing X

(NOTE: Report results of multiple completion on Well  
Completion or Rec completion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.)\*

1/11/87 - Ran 1.18' guide shoe, 44.09' shoe joint, .75' float collar,  
5 centralizers, 24 jts 8-5/8" 32# J-55 ST&C 1031.04', 74 jts  
8-5/8" 28# J-55 ST&C 3110.63', 2 jts 8-5/8" 32# J-55 ST&C  
88.15', 1 jt 8-5/8" 32# J-55 ST&C 14.55', total 4290.39',  
set at 4285'. Western cemented with 1400 sxs of PSL with  
5#/sxs Hi-Seal and 300 sxs of Cement. Circ 50 sxs. Displaced  
with 264 bbls FW. Did not bump plug. Float held at 10:15  
P.M.

ACCEPTED FOR RECORD

JAN 16 1987

CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Engr. Oprns. Sec.

DATE 1/13/87

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

\*See Instructions on Reverse Side