

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☒ Fee ☐
5. State Oil & Gas Lease No.
V-476

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- <input type="checkbox"/>	7. Unit Agreement Name Moonrise State Unit
2. Name of Operator Yates Petroleum Corporation	8. Farm or Lease Name
3. Address of Operator 105 South 4th St., Artesia, NM 88210	9. Well No. 1
4. Location of Well UNIT LETTER <u>M</u> <u>330</u> FEET FROM THE <u>South</u> LINE AND <u>330</u> FEET FROM THE <u>West</u> LINE, SECTION <u>27</u> TOWNSHIP <u>18S</u> RANGE <u>36E</u> NMPM.	10. Field and Pool, or WHdcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3795.5' GR	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER Set cmt retainer, squeeze, perforate ☒
Set CIBP, perforate, treat

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

5-8-87. TIH with Howco cement retainer and set at 5525'. Squeezed perforations 5578-85' w/75 sx Class "C" with .4% Halad-4 to 1900 psi.
5-9-87. WIH and perforated w/10.42" holes as follows: 5427-32' (6 holes) and 5446-49' (4 holes). Acidized perforations 5427-5449' w/1500 gals 7-1/2% NEFE acid and 15 ball sealers.
5-12-87. Set CIBP at 5370' w/35' cement on top. WIH and perforated 4514-22' w/9 .42" holes (1 SPF)
5-13-87. Acidized perforations 4514-4522' w/1500 gals 15% NEFE acid and 8 ball sealers.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED Jerry Sexton

TITLE Production Supervisor

DATE 5-14-87

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY _____

TITLE _____

DATE MAY 18 1987

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
MAY 15 1987
OCD
HOBBS OFFICE

RECEIVED MAY 15 1987
HOBBS OFFICE