

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. V-476	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name Moonrise State Unit
2. Name of Operator Yates Petroleum Corporation		8. Farm or Lease Name
3. Address of Operator 105 South 4th St., Artesia, NM 88210		9. Well No. 1
4. Location of Well UNIT LETTER <u>M</u> <u>330</u> FEET FROM THE <u>South</u> LINE AND <u>330</u> FEET FROM <u>West</u> LINE, SECTION <u>27</u> TOWNSHIP <u>18S</u> RANGE <u>36E</u> NMPM.		10. Field and Pool, or Wildcat Wildcat
15. Elevation (Show whether DF, RT, GR, etc.) 3795.5' GR		12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOBS <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> Set production casing, perforate, trt

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

TD 11025'. Ran 5-1/2" 15.5# J-55 casing set 5720'. Float shoe 5720' and float collar 5680'. Cemented with 925 sacks Class "C" with .5% CF-1 and 10% salt (yield 1.35, weight 15.0). PD 3:30 PM 4-30-87. Bumped plug to 2250 psi, released pressure, float and casing held okay. WOC 18 hrs.
Perforated 5578-85' w/8 .46" holes. Acidized perforations 5578-85' w/1000 gals 7-1/2% NEFE acid and 8 ball sealers.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Signed Paul Kants

TITLE Production Supervisor

DATE 5-6-87

Orig. Signed by
Paul Kants
Geologist

APPROVED BY _____

TITLE _____

DATE **MAY 15 1987**

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

MAY

R 1967

OCED
HOMES OFFICE

CHET

RECEIVED
MAY 1967