

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

API No. 30-025-29902

5a. Indicate Type of Lease	
State ☒	Fee ☐
5. State Oil & Gas Lease No.	
V-1987	

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT - A" (FORM C-101) FOR SUCH PROPOSALS.)

1. Name of Operator	
Phillips Petroleum Company	
2. Address of Operator	
4001 Penbrook Street, Odessa, Texas 79762	
3. Location of well	
UNIT LETTER <u>K</u>	1931 FEET FROM THE <u>south</u> LINE AND <u>1980</u> FEET FROM THE <u>west</u> LINE, SECTION <u>15</u> TOWNSHIP <u>18-S</u> RANGE <u>34-E</u> NMFM.

7. Unit Agreement Name
8. Farm or Lease Name
Airstrip A State
9. Well No.
1
10. Field and Pool, or Wildcat
North Airstrip - Bone Spring
11. County
Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON ☐	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☒	PLUG AND ABANDONMENT ☐
FULL OR ALTER CASING ☐	OTHER ☐	CASING TEST AND CEMENT JOBS ☒	

17. Descriptive Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

4-25-87: MI & RU.

4-26-87: Spud 17-1/2" hole at 8 A.M.. TD'd hole at 1 P.M. Set 13-3/8" 54.5# K-55 ST&C casing at 418'. Cemented with 425 sx Class "C", 2% CaCl₂. Circ 100 sx cmt. Cut off csg. Weld on 13-3/8" head. NU BOP. 561 cu ft. of slurry was pmpd, mixed at 68°, estimated temperature of formation in zone of interest was 65°, with cmt strength at time of casing test exceeding 500 psi. Total WOC 11.75 hrs.

4-27 thru

5-05-87: Drlg. TD'd 12-1/4" hole at 7:15 A.M. MST on 5-1-87. Set 8-5/8" casing at 4030' with 1400 sx Pace Setter Lite, 15#/sx salt, 1/4#/sx flocele + 200 sx Class C, 2% CaCl. Circ 35 sx cmt. WOC before testing 14.25 hrs.

6645' PTD

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. J. Mueller TITLE Engineering Supervisor, Reserv. DATE May 5, 1987

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY _____ TITLE _____ DATE MAY 11 1987

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
MAY 8 1987
OCD
HOBBS OFFICE