


CONDITION II-B 3000 W.P.
FOR AIR DRILLING OR
WHERE YATES AIR BLOWS ARE EXPECTED

H₂S TRIM REQUIRED
YES _____ NO _____



INSTALLATION CONTROL

MATERIAL LIST - CONDITION II - B
FOR AIR DRILLING

- A Texaco Wellhead
- B 3000 W.P. drilling spool with a 2" minimum flanged outlet for kill-line and 3" minimum flanged outlet for choke line
- C 3000 W.P. dual ram type preventer, hydraulic operated with 1" steel, 3000 W.P. control lines (where sub-structure height is adequate, 3-3000 W.P. single ram type preventers may be utilized.)
- D Rotating Head and extended Electric Line.
- 1,3,4, 7,8 2" minimum 3000 W.P. flanged full opening steel gate valve, or Halliburton Le Torr Plug valve.
- 2 2" minimum 3000 W.P. back pressure valve
- 3,4,9 3" minimum 3000 W.P. flanged full opening steel gate valve, or Halliburton Le Torr Plug valve.
- 12 3" minimum schedule 80, Grade "B", seamless line pipe
- 13 2" minimum x 3" minimum 3000 W.P. flanged cross
- 10, 11 2" minimum 3000 W.P. adjustable choke bodies
- 14 Cameron Mud Cough or equivalent (location optional in choke line.)

		TEXACO, INC. PRODUCING DEPARTMENT (CARTS) OIL AND GAS		
DESIGNED BY CHECKED BY APPROVED BY	DATE REV. NO. DES. NO.	EXHIBIT C		