

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

5a. Indicate Type of Lease
State ☐ Fee ☒
5. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER-		7. Unit Agreement Name
2. Name of Operator Chevron U.S.A. Inc.		8. Farm or Lease Name Carrie O. Davis
3. Address of Operator P.O. Box 670, Hobbs, NM 88240		9. Well No. 4
4. Location of Well UNIT LETTER <u>N</u> <u>890</u> FEET FROM THE <u>South</u> LINE AND <u>2310</u> FEET FROM THE <u>West</u> LINE, SECTION <u>29</u> TOWNSHIP <u>18S</u> RANGE <u>39E</u> NMPM.		10. Field and Pool, or Wildcat East Hobbs Field
15. Elevation (Show whether DF, RT, GR, etc.) 3590.8'		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

7. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Spud 12 1/4" hole 7-2-87. TD 12 1/4" hole 7-4-87. Run 8 5/8" 24# K-55 csg, set at 1860. Cmt w/400 sx Class C lead and tail w/800sx Class C. Displaced w/10# BW bumped plug; circ 183 sx to surf. Install csg head, test void area to 850psi, ok. NU BOP, install choke and kill lines, annular preventer, rotating head. Total WOC time: 55 hrs.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J. K. Elmire / J. M. Edkins TITLE STAFF DRILLING ENGINEER DATE JULY 14, 1987

ORIGINAL SIGNED BY JERRY SEXTON
DISTRICT I SUPERVISOR

APPROVED BY JUL 16 1987 DATE

CONDITIONS OF APPROVAL, IF ANY: