

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE
(Other instructions
verse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Mewbourne Oil Company

3. ADDRESS OF OPERATOR

P. O. Box 7698, Tyler, Texas 75711

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface

1980' FNL & 1650' FEL

14. PERMIT NO.

30-025-29954

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

3782.7' GR

5. LEASE DESIGNATION AND SERIAL NO

NM-0554244

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

FEDERAL "L"

9. WELL NO.

3

10. FIELD AND POOL, OR WILDCAT

Querecho Plains - Upper
Bone Springs

11. SEC., T., R., M., OR BLM. AND
SURVEY OR AREA

23-18S-32E

12. COUNTY OR PARISH

Lea

13. STATE

N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐

FRACTURE TREAT ☐

SHOOT OR ACIDIZE ☐

REPAIR WELL ☐

(Other) ☐

PULL OR ALTER CASING ☐

MULTIPLE COMPLETE ☐

ABANDON ☐

CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐

FRACTURE TREATMENT ☐

SHOOTING OR ACIDIZING ☐

(Other) Set Surface Casing ☒

REPAIRING WELL ☐

ALTERING CASING ☐

ABANDONMENT ☐

(NOTE: Report results of multiple completion on Well
Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Spud at 3:30 A.M. 6/19/87. 6/20/87 - Ran casing as follows:

1	notched collar	1.00'
1	13-3/8" shoe joint with insert float	28.63'
12	jts 13-3/8" 54.5#	421.06'
Total		450.69'

Set at 450'. Western cemented with 206 sxs Class "C" with 6% gel + 1/4#/sx Celloseal + 2% CaCl₂ followed by 210 sxs Class "C" Neet with 1/4#/sx Celloseal + 2% CaCl₂. Circ 36 sxs. Plug down to 421' at 12:30 A.M. 6/20/87.

ACCEPTED FOR RECORD

SJS
JUN 25 1987

CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED

Raymond Thompson

TITLE Engr. Oprns. Sec.

DATE 6/22/87

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side