

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
B-1306

SUNDRY NOTICES AND REPORTS ON WELLS
DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.

1. ☒ OIL WELL ☐ GAS WELL ☐ OTHER	7. Unit Agreement Name Central Vacuum Unit
2. Name of Operator Texaco Producing Inc.	8. Farm or Lease Name
3. Address of Operator P.O. Box 728, Hobbs, New Mexico 88240	9. Well No. 302
4. Location of Well UNIT LETTER <u>H</u> <u>2030</u> FEET FROM THE <u>North</u> LINE AND <u>1310</u> FEET FROM THE <u>East</u> LINE, SECTION <u>6</u> TOWNSHIP <u>18-S</u> RANGE <u>35-E</u> N.M.P.M.	10. Field and Pool, or Wildcat Vacuum Grayburg San Andres
15. Elevation (Show whether DF, RT, GR, etc.) 3972 GR	12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☐
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPER. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☐ COMPLETION ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1703.

TOTAL DEPTH 4720'

20" 169' K-55 CASING SET AT 350'
13-3/8" 54.5' K-55 CASING SET AT 1545'
9-5/8" 36-40' J-55 CASING SET AT 2778'
7" 23' J-55 CASING SET AT 4320'
6-1/4" OPEN HOLE AT 4320' - 4720'

1. MIRU 10-16-87. Install BOP. Retrieve 7" RBP at 3782'. TIH with 6 1/4" bit to 4720' TD. POH.
2. Run Compensated Neutron / Gamma Ray / Caliper / Casing Collar / Cement Bond Log.
3. Displace hde with 2 1/2 KCL water. Spot 630 gallons 15% NEFE HCL across open hole.
4. Acidize open hole 4320'-4720' with 6870 gallons 15% NEFE, 2250 pounds rock salt, and 110 gallons TH756 scale inhibitor in four stages. AIR 4.5 BPM, Max TP 2900*, ISIP 2200*.
5. Install rod pumping equipment. On 24 hour OPT 11-1-87: pumped 42 BO, 3 BW, gravity 38.1, GOR 606.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED A. Gernandt 393-4031 TITLE Area Superintendent DATE 11-5-1987

Orig. Signed by
Paul Kautz

APPROVED BY Geologist TITLE Geologist DATE NOV 11 1987

CONDITIONS OF APPROVAL, IF ANY: