

UNITED STATES OF AMERICA
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

Form approved
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐		3. LEASE DESIGNATION AND SERIAL NO. NM-21172	
2. NAME OF OPERATOR Harvey E. Yates Company		4. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR P.O. Box 1933, Roswell, New Mexico 88201		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface 330' FNL & 330' FEL		8. FARM OR LEASE NAME Sheldon 15 Federal	
14. PERMIT NO. 30-025-30031		9. WELL NO. #1	
15. ELEVATIONS (Show whether OF, RT, CR, etc.) 3971.2 GL		10. FIELD AND POOL, OR WILDCAT Mescalero Escarpe	
		11. SEC., T., R., N., OR S.E. AND SURVEY OR AREA Sec. 15, T18S, R33E	
		12. COUNTY OR PARISH Lea	13. STATE NM

Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	☐	WATER SHUT-OFF	☐
FRACTURE TREAT	☐	REPAIRING WELL	☐
SHOOT OR ACIDIZE	☐	ALTERING CASING	☐
REPAIR WELL	☐	ABANDONMENT*	☒
(Other)	☐	(Other) Spud, Surface & Inter. Csg	☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

8/28/87 Spud well @ 11:45 am
Ran 10 jts 13 3/8, 54.5, J55 csg, set @ 415 ft.
Cement w/400 sks Class 'C' w/2% CaCl & 1/4# celloflake.
Plug down @ 8:20 pm 8/28/87, Circ 85 sks to pit. WOC 12 hrs
Test BOP-600 psi/30 min-Held ok

8/31/87 Ran 75 jts 8 5/8, 24 & 32#, J55 csg. DV tool @ 1790 ft.
1st Stage: 300 sks Litewate & 200 sks Class 'C' w/2% CaCl.
Circ 50 sks to pit. Plug down @ 5:45 pm 8/31/87
2nd Stage: 430 sks Litewate & 100 sks Class 'C' w/2% CaCl.
Circ 15 sks to pit. WOC 12 hrs.
Test BOP-1200 psi/30 min-Held ok

ACCEPTED FOR RECORD

SEP 21 1987

SJS

CARLSBAD, NEW MEXICO

18. I hereby certify that the foregoing is true and correct

SIGNED [Signature] NM Young TITLE Drilling Superintendent DATE 9/3/87

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side