

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S		
LAND OFFICE		
OPERATOR		

API No. 30-025-30070

5a. Indicate Type of Lease
State ☒ Fee ☐

5. State Oil & Gas Lease No.
B-2229

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR,
USE "APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

11. OIL WELL ☒ GAS WELL ☐ OTHER ☐

12. Name of Operator
Phillips Petroleum Company

7. Unit Agreement Name

8. Farm or Lease Name
Philmex

13. Address of Operator
4001 Penbrook Street, Odessa, Texas 79762

9. Well No.
27

14. Location of Well
UNIT LETTER F 1980 FEET FROM THE North LINE AND 1980 FEET FROM
THE West LINE, SECTION 26 TOWNSHIP 17-S RANGE 33-E NMPM

10. Field and Pool, or Wildcat
Maljamar/Gb/SA

15. Elevation (Show whether DF, RT, GR, etc.)
4140' GR

12. County
Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER Well Completion ☒

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

2-23-88: MI. RU WSU. Tst'd BOP & csg to 3000#. Perf'd using 4" OD csg gun 2SPF from:

4218'-4221'	3'	6 holes	2 SPF	4451'-4453'	2'	4 holes	2 SPF
4235'-4244'	9'	18 holes	2 SPF	4473'-4482'	9'	18 holes	2 SPF
4254'-4257'	3'	6 holes	2 SPF	4498'-4516'	18'	36 holes	2 SPF
4294'-4297'	3'	6 holes	2 SPF	4523'-4535'	12'	24 holes	2 SPF
4300'-4305'	5'	10 holes	2 SPF	4540'-4543'	3'	6 holes	2 SPF
4336'-4348'	12'	24 holes	2 SPF	4548'-4550'	2'	4 holes	2 SPF
4358'-4361'	3'	6 holes	2 SPF	4594'-4607'	13'	26 holes	2 SPF
4369'-4472'	3'	6 holes	2 SPF				
4376'-4378'	2'	4 holes	2 SPF				
4380'-4382'	2'	4 holes	2 SPF				
4408'-4410'	2'	4 holes	2 SPF				
4428'-4434'	6'	12 holes	2 SPF				

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. J. Mueller TITLE Engineering Supervisor, Resv. DATE 3-18-88

ORIGINAL SIGNED BY JERRY SEXTON

APPROVED BY DISTRICT 1 SUPERVISOR TITLE DATE MAR 23 1988

CONDITIONS OF APPROVAL, IF ANY:

2-24-88:
2-25 thru
3-09-88:
3-10-88:
3-11 thru
3-15-88:

Acidized perfs w/11,200 gals 15% NEFe HCl containing fines
suspension agent and clay stabilizer. Flwd & swbd back 458 BLM
and acid.

Frac'd perfs w/112,000 gals gelled crosslinked 2% KCl wtr &
222,000# 20/40 mesh sand. Swbd back load.

WIH w/2-7/8" tbg, SN @ 4650', TAC @ 4138'.

WIH w/2-1/2" X 1-1/4" X 16' pmp. Pmpg - no test.

RECEIVED

MAR 22 1988

OCD
HOBBS OFFICE