

STATE OF NEW MEXICO
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

API No. 30-025-30078

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No B-2148
7. Unit Agreement Name
8. Farm or Lease Name Leamex
9. Well No. 41
10. Field and Pool, or Wildcat Maljamar Gb/SA
12. County Lea

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR, USE "APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS.)

11. OIL WELL ☒ GAS WELL ☐ OTHER ☐

12. Name of Operator
Phillips Petroleum Company

13. Address of Operator
4001 Penbrook Street, Odessa, Texas 79762

14. Location of Well
UNIT LETTER D 860 FEET FROM THE North LINE AND 660 FEET FROM THE West LINE, SECTION 22 TOWNSHIP 17-S RANGE 33-E NMPM

15. Elevation (Show whether DF, RT, GR, etc.)
4167' GR, 4176' RKB

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input checked="" type="checkbox"/>	OTHER <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

10-27 thru

11-02-87: Core #2 4350'-4410'
Core #3 4410'-4457'
Core #4 4457'-4491'
Core #5 4491'-4551'
Core #6 4551'-4582'

11-03-87: Td'd 7-7/8" hole @ 9 A.M. @ 4800'. Ran DLL-MSFL-GR-Ca1, CNL-LDT-GR-Ca1 Td to 2500', CNL-GR-Ca1 2500'-0.

See Reverse side

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. J. Mueller TITLE Engineering Supervisor, Resv. DATE 11/13/87

APPROVED BY ORIGINAL SIGNED BY JERRY SEXTON TITLE DISTRICT 1 SUPERVISOR DATE NOV 16 1987

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED
 NOV 10 1981
 HOBB'S OFFICE

Set 5-1/2" 15.5# K-55 ST&C @ 4800' w/ 1500 sx Howco Lite, 5% salt, 400 sx Class C Neat. Circ. 400 sx cmt. ND BOP.

11-04-87:

11-05 thru

11-10-87:

11-11-87:

Install BOP, tested BOP & csg. to 3000 pst. Ran GR/collar locator log. Perf'd using 4" OD csg. gun 2 SPF from -

4214'-4220'	6'	12 holes	2 SPF
4274'-4281'	7'	14 holes	2 SPF
4312'-4318'	6'	12 holes	2 SPF
4365'-4368'	3'	6 holes	2 SPF
4388'-4394'	6'	12 holes	2 SPF
4406'-4408'	2'	4 holes	2 SPF
4416'-4418'	2'	4 holes	2 SPF
4422'-4425'	3'	6 holes	2 SPF
4432'-4434'	2'	4 holes	2 SPF
4438'-4444'	6'	12 holes	2 SPF
4447'-4461'	14'	28 holes	2 SPF
4480'-4482'	2'	4 holes	2 SPF
4493'-4497'	4'	8 holes	2 SPF
4514'-4516'	2'	4 holes	2 SPF
4546'-4549'	3'	6 holes	2 SPF
4563'-4566'	3'	6 holes	2 SPF
4576'-4580'	4'	8 holes	2 SPF
TOTAL	75'	150 holes	