

WRS COMPLETION REPORT

COMPLETIONS SEC 22 TWP 17S RGE 33E
PI# 30-T-0014 01/25/88 30-025-30078-0000 PAGE 1

NMEX LEA * 860FNL 660FWL SEC NW NW
STATE COUNTY FOOTAGE SPOT
PHILLIPS PET D DO
OPERATOR WELL CLASS INIT FIN
41 LEAMEX
WELL NO. LEASE NAME
4176KB 4168GR MALJAMAR
OPER ELEV FIELD/POOL/AREA
API 30-025-30078-0000
LEASE TYPE/NO. PERMIT OR WELL I.D. NO.
10/18/1987 12/04/1987 ROTARY OIL
SPUD DATE COMP. DATE TYPE TOOL STATUS
4900 GRBG-SAD LA RUE C E 2 RIG SUB 7
PROJ. DEPTH PROJ. FORM CONTRACTOR
DTD 4800 PB 4748 FM/TD SN ANDRS
DRILLERS T.D. LOG T.D. PLUG BACK TD OLD T.D. FORM T.D.

LOCATION DESCRIPTION

7 MI SE MALJAMAR, NM

CASING/LINER DATA

CSG 8 5/8 @ 1490 W/ 1000 SACKS
CSG 5 1/2 @ 4800 W/ 1900 SACKS

TUBING DATA

TBG 2 3/8 AT 4596

INITIAL POTENTIAL

IPP 58BOPD 72 MCFD 15BW 24HRS
GRAYBURG PERF W/ 2/FT 4214- 4497 GROSS
SN ANDRS PERF W/ 2/FT 4514- 4580 GROSS
GTY 37.9 GOR 1241
RESV- GRAYBURG-SAN ANDRES
COMMINGLED

TYPE	FORMATION	LTH	TOP DEPTH/SUB	BSE DEPTH/SUB
LOG	SALT		1632 2544	2610 1566
LOG	QUEEN		3744 432	
LOG	GRAYBURG		4160 16	
LOG	SN ANDRS		4508 -332	

CONTINUED IC# 300257030187

Copyrighted 1988
Petroleum
Information Corporation

Petroleum Information

DB a company of
The Dun & Bradstreet Corporation

PI-WRS-GET
Form No 187

COMPLETIONS SEC 22 TWP 17S RGE 33E
PI# 30-T-0014 01/25/88 30-025-30078-0000 PAGE 2

PHILLIPS PET 41 LEAMEX D DO

CORES

CORE 1	4290-	4350 REC 60.00FT GRAYBURG CONV	D
NO DESCRIPTION AVAILABLE			
CORE 2	4350-	4410 REC 60.00FT GRAYBURG CONV	D
NO DESCRIPTION AVAILABLE			
CORE 3	4410-	4457 REC 47.00FT GRAYBURG CONV	D
NO DESCRIPTION AVAILABLE			
CORE 4	4457-	4491 REC 39.00FT GRAYBURG CONV	D
NO DESCRIPTION AVAILABLE			
CORE 5	4491-	4551 REC 60.00FT GRBG-SAD CONV	D
NO DESCRIPTION AVAILABLE			
CORE 6	4551-	4590 REC 39.00FT SN ANDRS CONV	D
NO DESCRIPTION AVAILABLE			

PRODUCTION TEST DATA

PTS 5BO							2HRS
GRAYBURG PERF		W/	2/FT	4214-	4497	GROSS	
SN ANDRS PERF		W/	2/FT	4514-	4580	GROSS	
PERF 4214-	4220	4274-	4281	4312-	4318	4365-	4368
PERF 4388-	4394	4406-	4408	4416-	4418	4422-	4425
PERF 4432-	4434	4438-	4444	4447-	4461	4480-	4482
PERF 4493-	4497	4514-	4516	4546-	4549	4563-	4566
PERF 4576-	4580						
ACID 4214-	4580	7500GALS					
15% NEFE HCL							
SWBD 5 BO + 8 BLW & SWBD DRY IN 2 HRS							
PERF W/150 SHOTS							
COMMINGLED							

PTS	220BW		
GRAYBURG PERF		4214-	4497 GROSS
SN ANDRS PERF		4514-	4580 GROSS
SWFR 4214-	4580	84000GALS	160000LBS SAND
			ADDTVGELA
X-LINK 2% KCL	20/40 MESH		
SWBD 220 BW IN 1 RUN			

CONTINUED

COMPLETIONS SEC 22 TWP 17S RGE 33E
PI# 30-T-0014 01/25/88 30-025-30078-0000 PAGE 3

PHILLIPS PET LEAMEX D DO
41

PRODUCTION TEST DATA

COMMINGLED

LOGS AND SURVEYS /INTERVAL,TYPE/

LOGS	2500-	4800	DLL	2500-	4800	MSFL	2500-	4800	GR
LOGS	2500-	4800	CAL	2500-	4800	CNL	2500-	4800	LDT
LOGS	0-	2500	CNL	0-	2500	GR	0-	2500	CAL

DRILLING MEDIA /TYPE,DEPTH/

2685	10.0	4457	10.1	PPG
------	------	------	------	-----

DRILLING PROGRESS DETAILS

	PHILLIPS PET
	4001 PENBROOK RM 401
	ODESSA, TX 79762
	915-367-1266
09/29	LOC/1987/
10/22	DRLG 2685 (SALT, ANHY), VIS 28
10/29	CRG 4382
10/30	DRLG 4457 (DOLO), VIS 30
11/10	4800 TD, WOCT
11/18	4800 TD, PB 4748, TSTG
11/20	4800 TD, PB 4748, TSTG
	TD REACHED 11/03/87 RIG REL 11/04/87
01/21	4800 TD, PB 4748
	COMP 12/4/87, IPP 58 BO, 72 MCFG, 15 BWPD,
	GOR 1241, GTY 37.9
	PROD ZONE - GRAYBURG-SAN ANDRES 4214-4580
	SIX CORES, NO DSTS RPTD