

UNITED STATES DEPARTMENT OF THE INTERIOR  
BUREAU OF LAND MANAGEMENT

Form approved.  
Budget Bureau No. 1004-0135  
Expires August 31, 1985

3. LEASE DESIGNATION AND SERIAL NO.  
NM-0554244

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different depth. Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐  
2. NAME OF OPERATOR  
Mewbourne Oil Company  
3. ADDRESS OF OPERATOR  
P. O. Box 7698, Tyler, Texas 75711  
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)  
At surface  
660' FNL & 1650' FEL  
14. PERMIT NO.  
API #30-025-30129  
15. ELEVATIONS (Show whether DF, RT, GR, etc.)  
3789.2'

7. UNIT AGREEMENT NAME  
8. FARM OR LEASE NAME  
FEDERAL "L"  
9. WELL NO.  
4  
10. FIELD AND POOL, OR WILDCAT  
Querecho Plains - Upper Bone Springs  
11. SEC., T., R., M., OR BLE. AND SURVEY OR AREA  
23-18S-32E  
12. COUNTY OR PARISH  
Lea  
13. STATE  
N.M.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐ PULL OR ALTER CASING ☐  
FRACTURE TREAT ☐ MULTIPLE COMPLETE ☐  
SHOOT OR ACIDIZE ☐ ABANDON\* ☐  
REPAIR WELL ☐ CHANGE PLANS ☐  
(Other) ☐

WATER SHUT-OFF ☐ REPAIRING WELL ☐  
FRACTURE TREATMENT ☐ ALTERING CASING ☐  
SHOOTING OR ACIDIZING ☐ ABANDONMENT\* ☐  
(Other) ☒ Set Production String

(Note: Report results of multiple completion on Well Completion or Re-completion Report and Log form.)

17. DESCRIBE PROMISED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

11/12/87 - Ran casing as follows:

1	Down-jet float shoe	2.00'
1	8-5/8" 32# LS shoe	37.57'
1	float collar	1.63'
47	jts 8-5/8" 32# LS	2099.12'
47	jts 8-5/8" 24# LS	2029.06'
4	jts 8-5/8" 32# LS	178.63'
	Total	4348.01'
	Set @	4318.00'

Western cemented with 1300 sxs of Class "C" with 6% gel + 1#/sx celloseal followed by 300 sxs of Class "C" with 1% CaCl<sub>2</sub>. PD to 4287' at 2:00 AM. 11/12/87. Circulated 50 sxs. Floats held.

18. I hereby certify that the foregoing is true and correct

SIGNED Raymond Thompson TITLE Engr. Oprns. Sec. DATE 11/12/87

(This space for Federal or State office use)

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_  
CONDITIONS OF APPROVAL, IF ANY:

ACCEPTED FOR RECORD

NOV 17 1987

\*See Instructions on Reverse Side SJS

EL PASO, NEW MEXICO

HOBBS OFFICE  
OCD  
NOV 18 1987  
RECEIVED