

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE
(Other instructions on
reverse side)

Form approved.
Budget Bureau No. 1004-0135
Expires August 31, 1985

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. <input checked="" type="checkbox"/> OIL WELL <input type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER		5. LEASE DESIGNATION AND SERIAL NO. NM 26884-A	
2. NAME OF OPERATOR OXY USA Inc.		6. IF INDIAN, ALLOTTEE OR TRIBE NAME	
3. ADDRESS OF OPERATOR P. O. Box 50250, Midland, TX 79710		7. UNIT AGREEMENT NAME	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 2310' FNL & 330' FEL		8. FARM OR LEASE NAME Federal AG	
14. PERMIT NO. 30-025-30326		9. WELL NO. 2	
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 3924 GR		10. FIELD AND POOL, OR WILDCAT Wildcat (Wolfcamp)	
		11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA Sec. 8-T18S-R33E	
		12. COUNTY OR PARISH Lea	
		13. STATE NM	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
TEST WATER SHUT-OFF	<input type="checkbox"/>	WATER SHUT-OFF	<input type="checkbox"/>
FRACTURE TREAT	<input type="checkbox"/>	REPAIRING WELL	<input type="checkbox"/>
SHOOT OR ACIDIZE	<input type="checkbox"/>	ALTERING CASING	<input type="checkbox"/>
REPAIR WELL	<input type="checkbox"/>	ABANDONMENT*	<input type="checkbox"/>
(Other)	<input type="checkbox"/>	(Other) Running intermediate casing	<input checked="" type="checkbox"/>

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

T.D. 3280' Dolomite. Prep to drill ahead. Drilled a 12 1/4" hole from 365' to a T.D. of 3280' in Dolomite. Ran and set 56 joints (2339.26) of 8 5/8" OD 24# casing and 19 joints (814.13') of 8 5/8" OD 32# casing @ 3175.42' and cemented w/850 sacks 15# salt 1/4# Flocele 5# Gilsonite and 300 sacks Class C neat cement. PD @ 1130 MDT on 4-13-88. Circulated 150 sacks cement to the surface. WOC 18 hours. Tested the 8 5/8" OD casing to 1000# for 30 minutes - OK.

18. I hereby certify that the foregoing is true and correct

SIGNED J. A. Ingram TITLE Dist. Oper. Mgr. - Prod. DATE 4-14-88

(This space for Federal or State office use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side

SJS

RECEIVED
MAY 2 1988
OCD
NIOBBS OFFICE