

DEPARTMENT OF THE INTERIOR

BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different formation. Use "APPLICATION FOR PERMIT" for such proposals.)

OIL WELL ☒ GAS WELL ☐ OTHER ☐

NAME OF OPERATOR

Siete Oil & Gas Corporation

ADDRESS OF OPERATOR

P.O. Box 2523

Roswell, NM 88202

LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.)

At surface

660' FNL & 330' FWL, Unit Letter D

16. PERMIT NO.

30-025-30346

18. ELEVATIONS (Show whether of, to, or on etc.)

3707' KB

NM-9016

1. IF APPLICABLE, ALLOTMENT OR TRACT NAME

2. DATE OF ACQUISITION DATE

3. NAME OF LEASE FORM

Inch Federal

4. WELL NO.

10

10. FIRM AND FIRM, OR WILDCAT

E. Shugart Delaware

11. SEC. T. R. N. OR BLS. AND QUARTER OR AREA

Sec. 30: T18S, R32E

12. COUNTY OR PARISH

Lea

13. STATE

NM

19. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

FRACTURE TREAT

SHOOT OR ACIDIZE

REPAIR WELL

(Other)

PILL OR ALTER CASING

MULTIPLE COMPLETION

ABANDON*

CHANGE PLANE

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

FRACTURE TREATMENT

SHOOTING OR ACIDIZING

(Other)

DETAILING WELL

ALTERING CASING

ABANDONMENT*

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

20. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface latitudes and measured and true vertical depths for all markers and zones pertinent to this work.)

6/12/88 Amend TD from 6500' to 6650'.

6/14/88 Reached TD 6650' on 6/14/88 @ 11:45 AM, RU Schlumberger, ran CNL-LDT-FDC, DLL-MSFL, EPT & Sonic logs from TD to 2400'. Well determined non-commercial. Plug and abandon as follows:

Set cement plugs:

1. 30 sx plug from 6595'-6495' (100')
2. 38 sx plug from 4746'-4646' (100')
3. 34 sx plug from 3570'-3470' (100')
4. 129 sx plug from 2270'-2070' (200')
5. 68 sx plug from 1100'-1000' (100')
6. 38 sx plug from 435'-335' (100')
7. 16 sx plug from 50'-surface (50')

Release rig @ 4:15 AM on 6/16/88.

BLM verbal approval received from Mr. Shannon Shaw on 6/15/88.

RECEIVED
JUN 23 10 50 AM '88
CANYON AREA OFFICE

21. I hereby certify that the foregoing is true and correct

SIGNED [Signature]

TITLE Production/Reservoir Engineer DATE 6/16/88

(This space for Federal or State office use)

APPROVED BY [Signature]
CONDITIONS OF APPROVAL, IF ANY:

TITLE [Signature] DATE 6-27-88

Liability on
surface record

*See Instructions on Reverse Side