## STATE OF NEW MEXICO **ENERGY AND MINERALS DEPARTMENT**

## OIL CONSERVATION DIVISION P O BOX 2088

NO OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S G.S	
LAND OFFICE	
OPERATOR	

DISTRIBUTION	SANTA FE, NEW MEX	ICO 87501		Form C-103
SANTA FE				Revised 10-1-78
FILE				
U.S G.S			5a. Indicate Type of Le	ase
LAND OFFICE		ĺ	State 🔀	Fee 🗌
OPERATOR	101 " 00 00- 0-0		5. State Oil & Gas Leas	e No
	API # 30-025-30394		B-2229	
	OTICES AND REPORTS ON WELLS			
USE *APPLICATION	ALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIF FOR PERMIT - * (FORM C 101) FOR SUCH PROPOSALS	FERENT RESERVOIR,		111111111
OIL GAS WELL X WELL	OTHER		7. Unit Agreement Na	me
12 Name of Operator			8. Farm or Lease Name	•
Phillips Petroleum Compa	ny,		Philmex	
Room 401, 4001 Penbrook S	itreet, Odessa, Texas 79:	762	9. Well No.	
14 Location of Well			10. Field and Pool, or V	Mildan
UNIT LETTER N . 660	FEET FROM THE SOUTH LINE AND	1880	Maljamar Gb/	
		<b>.</b>		
THE West LINE, SECTION 26	TOWNSHIP 17-S RANG	E_33-E NMPM		
······································				
///////////////////////////////////////	5. Elevation (Show whether DF, RT, GR, e	1	12. County	
111111111111111111111111111111111111111	4129.6'GR (Unprepared	)	Lea	
16 Check Appropr	ate Box To Indicate Nature of No	tice, Report or Oth	er Data	
NOTICE OF INTENTION T			ENT REPORT OF:	
PERFORM REMEDIAL WORK		300312001	HAT KEPOKT OF.	
3	PLUG AND ABANDON	DIAL WORK	ALTERING	CASING
<u> </u>	COMI	MENCE DRILLING OPNS.	PLUG AND	ABANDONMENT [
PULL OR ALTER CASING	CHANGE PLANS CASIN	G TEST AND CEMENT JOB		
OTHER	ОТН	Perf & tre	eat	X
17 Describe Proposed or Completed Operation work) SEE RULE 1103	s (Clearly state all pertinent details, and	give pertinent dates, inc	cluding estimated date	of starting any propose
7-05-88: RU WSU, installed 3000 p 2 SPF from 4194'-4612' (1	osi BOP, tst'd BOP & casing. Ran (	GR from 4755'to 350	00'. Perf'd 5-1/2" cs	sg w/4" csg gun
23/17/01/17/34 -40/2 (	31 - 202 SHO(\$).			
7-06 thru				
7-11-88: Acidized perfs w/13,200	gals 15% NEFe HCl containing fir	es suspension ager	nt and clay stabilize	r Frac'd nerfs
w/135,000 gals gelled 30	# crosslinked 2% KCl wtr; 230,0(	0# 20/40 mesh san	d and 28,000# 20/4	0 mesh
Santrol resin-coated sand	<b>J</b> .		•	
7-12 thru				
	0" 4h - @ 45101 - 12" V 4 414" V	-		
3wbg back lead. Set 2-3/	8" tbg @ 4618' and 2" X 1-1/4" X	18' pmp. Pmpg to	frac tank.	
$\bigcirc$				
/ /				
18 I bereby castify that the information above is true and cor	nplete to the best of my knowledge and belief.			
SIGNED W.J.I	Mueller Engineering	Supervisor, Resv.		7 21 00
	vidence title Engineering		DATE _	7-21-88
APPROVED BY	TITLE		DATE	A. Carrier