

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P. O. BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S		
LAND OFFICE		
OPERATOR		

API No. 30-025-30397

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>	
5. State Oil & Gas Lease No. B-2229	
7. Unit Agreement Name	
8. Farm or Lease Name Philmex	
9. Well No. 33	
10. Field and Pool, or Wildcat Maljamar Gb/SA	
12. County Lea	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

11. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>
12. Name of Operator Phillips Petroleum Company
13. Address of Operator 4001 Penbrook Street, Odessa, Texas 79762
14. Location of Well UNIT LETTER <u>B</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>1980</u> FEET FROM THE <u>East</u> LINE, SECTION <u>28</u> TOWNSHIP <u>17-S</u> RANGE <u>33-E</u> NMPM

15. Elevation (Show whether DF, RT, GR, etc.)  
4178' GR

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <u>Perf'd &amp; treated</u> <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103

7-29-88: Perf'd 5-1/2" csg w/4" OD @ 2 SPF from 4138'-4580' (48'-96 holes).

7-30 thru

8-14-88: Acidized perms w/5000 gals 15% NEFe HCl w/clay stabilizer. Frac'd perms w/48,400 gals gelled 30# crosslinked 2% KCl wtr and 91,000# 20/40 mesh Ottawa sand. Swbd & flwd back load.

8-15-88: Set 2-3/8" tbg @ 4500' and pump.

8-15 thru

9-01-88: Pumping 24 hrs. a day.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] W J Mueller TITLE Engineering Supervisor, Resv. DATE 9/7/88  
APPROVED BY Paul Kautz Geologist TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY.