## STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

13 Address of Operator

14 Location of Weil

## OIL CONSERVATION DIVISION

Form C-1	103
Revised	10-1-78

9. Well No.

50

12. County

10. Field and Pool, or Wildcat Maljamar Gb/SA

NO OF COPIES RECEIVED	D	P O BOX 2088	
DISTRIBUTION		SANTA FE, NEW MEXICO 8	37501 Fo Re
SANTA FE			Ne.
FILE			Es ladasta Tara flanca
U.S.G.S		_	5a. Indicate Type of Lease
LAND OFFICE			State <b>⊠</b>
OPERATOR		API No. 30-025-30427	5. State Oil & Gas Lease No B-2148
(DO NOT US	THIS FORM FOR PROP	NOTICES AND REPORTS ON WELLS POSALS TO DRIEL ON TO . THE PLAN OR PLUG BACK TO A DIFFERENT F ON FOR PERMIT (LOHM C 101) FOR SUCH PROPOSALS )	HE SE HVOIR.
OIL WELL	GAS WELL	OTHER	7. Unit Agreement Name
Name of Operator Phillips Petr	roleum Com	pany	8. Farm or Lease Name Leamex

UNIT LETTER K 1650 FEET FROM THE SOUTH LINE AND 1980 FEET FROM

15 Elevation (Show whether DF, RT, GR, etc.)

THE West LINE, SECTION 21 TOWNSHIP 17-S RANGE 33-E

		4182.4' GR (Ur	prepa	red)	Lea		
6	Check Appropria	te Box To Indicate	Nature	of Notice, Report or	Other Data		
NOTI	CE OF INTENTION TO	<b>D</b> :		SUBSEC	QUENT REPORT	OF:	
PERFORM REMEDIAL WORK		PLUG AND ABANDON		REMEDIAL WORK		ALTERING CASING	
TEMPORARILY ABANDON				COMMENCE DRILLING OPNS.	$\boxtimes$	PLUG AND ABANDONMENT	
PULL OR ALTER LASING		CHANGE PLANS		CASING TEST AND CEMENT JOB	×		
OTHER				OTHER			$\Box$

17 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103

8-02-88: Spud 12-1/4" hole @ 1:00 p.m. MST.

4001 Penbrook Street, Odessa, Texas 79762

8-03 thru

TD'd 12-1/4" hole @ 9:45 a.m. MST on 8-3-88. Set 8-5/8" 24# K-55 ST&C csg @ 1467' w/1000 sx Class "C" cmt w/2% CaCl. Circ. 297 sx cmt. Temperature of cmt. slurry 85°, formation temperature in zone of interest 65°. Estimated cmt strength @ time of csg test exceeded 2000 psi. Total WOC time 9-1/2 hrs. Td'd 7/8" hole @ 9:45 a.m. MST on 8-7-88. Ran CNL-LDT-GR/Cal from TD @ 4700' to surface; DLL-MSFL-GR/Cal from TD to 2500' and Differential Temp - GR logs from 4700'-3500'. Set 5-1/2" 15.5# K-55 ST&C csg @ 4700' w/1200 sx Howco Lite, 5% salt + 300 sx "C" Neat. Circ. 232 sx cmt. Released rig 5:15 p.m. MST 8-8-88.

18 thereby certify that the information above is true and complete to the bes	st of my kn	owledge and belief.		· · · · · · · · · · · · · · · · · · ·
SIGNED W J Mueller	*171.6	Engineering Supervisor, Resv	DATE	8/10/88
ORIGINAL SIGNED BY JERRY SEXTON APPROVED BY DISTRICT I SUPERVISOR	OTLE		DATE	AUG 1.5'08