

STATE OF NEW MEXICO  
ENERGY AND MINERALS DEPARTMENT

OIL CONSERVATION DIVISION

P O BOX 2088  
SANTA FE, NEW MEXICO 87501

Form C-103  
Revised 10-1-78

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S		
LAND OFFICE		
OPERATOR		

API No. 30-025-30453

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. B-2148	
7. Unit Agreement Name	
8. Farm or Lease Name Leamex	
9. Well No. 53	
10. Field and Pool, or Wildcat Maljamar Gb/SA	
12. County Lea	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR,  
USE "APPLICATION FOR PERMIT - " (FORM C-101) FOR SUCH PROPOSALS)

11. OIL WELL ☒ GAS WELL ☐ OTHER ☐

12. Name of Operator  
Phillips Petroleum Company

13. Address of Operator  
4001 Penbrook Street, Odessa, Texas 79762

14. Location of Well  
UNIT LETTER F 1980 FEET FROM THE North LINE AND 1980 FEET FROM  
THE West LINE, SECTION 25 TOWNSHIP 17-S RANGE 33-E NMPM

15. Elevation (Show whether DF, RT, GR, etc.)  
4115.5' GR (Unprepared)

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☒ OTHER ☐

17 Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

9-24-88: Spud 12-1/4" hole @ 2:45 p.m. MST.

9-25-88: Td'd 12-1/4" hole @ 2:00 p.m. Set 8-5/8" 24# K-55 ST&C csg. @ 1512' w/1000 sx "C", 2% CaCl. Circ. 55 sx. Formation temperature in zone of interest 65°, temperature of cmt. slurry 80°. Cement strength @ time of csg. test exceeded 1000 psi. Total time WOC 10 hrs.

9-26 thru  
9-29-88: Drlg.

9-30-88: Td'd 7-7/8" hole @ 7:23 p.m. MST. Ran CNL-LDT-GR-Cal from TD @ 4800' to 2500' and CNL-GR-Cal from 2500' to surface.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. J. Mueller TITLE Engineering Supervisor, Resv. DATE 10/10/88

ORIGINAL SIGNED BY JERRY S. GORMAN

APPROVED BY DISTRICT SUPERVISOR TITLE  DATE

CONDITIONS OF APPROVAL, IF ANY:

Set 5-1/2" 15.5# K-55 ST&C csg. @ 4800' w/1200 SX Howco Lite  
w/5% salt + 300 SX Class "C" Neat. Circ. 200 SX cmt. Released  
rig @ 8:00 p.m.  
Notified Hobbs-NMOCB on 9-28-88 of waterflow @ 3795'-85 BPH.

RECEIVED  
OCT 17 1988  
HOBBS OFFICE