

OIL CONSERVATION DIVISION
P. O. BOX 2088
SANTA FE, NEW MEXICO 87501

Form C-103
Revised 10-1-78

NO. OF COPIES RECEIVED		
DISTRIBUTION		
SANTA FE		
FILE		
U.S.G.S.		
LAND OFFICE		
OPERATOR		

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Terra Resources, Inc.		8. Farm or Lease Name Terra Enron 13 State
3. Address of Operator 10 Desta Drive, Suite 500 West, Midland, Texas 79705		9. Well No. 1
4. Location of Well UNIT LETTER <u>A</u> <u>660</u> FEET FROM THE <u>North</u> LINE AND <u>660</u> FEET FROM THE <u>East</u> LINE, SECTION <u>13</u> TOWNSHIP <u>18S</u> RANGE <u>34E</u> NMPM.		10. Field and Pool, or Wildcat Vacuum Abo Reef
15. Elevation (Show whether DF, RT, GR, etc.) 3976 GR		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>	CASING TEST AND CEMENT JOBS <input checked="" type="checkbox"/>	OTHER <input type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Intermediate 8-5/8" casing set on 9/26/83 to a depth of 3300'.
941' 32# K-55 ST&C
2374' 24# K-55 ST&C

Cemented with 1200 sx Pacesetter Lite Class "C", 1/4#/sx Cellophane tail: 250 sx Class "C" with 2% CaCl₂.

Flood held.

Circulated 361 sx cement to pit.

Centralizers: 3271, 3186, 3058, 2932, 2804, 334.

WOC 16 hrs.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED C. Robert Wankler TITLE OPERATIONS ENGINEER DATE 9/27/88

ORIGINAL SIGNED BY W. A. WILSON

APPROVED BY DISTRICT MANAGER TITLE DISTRICT MANAGER DATE

CONDITIONS OF APPROVAL, IF ANY:

RECEIVED

SEP 28 1988

ODD
HOBBS OFFICE