STATE OF NEW MEXICO ENERGY AND MINERALS DEPARTMENT

CHOL MIG HILLEN WED DE		
DISTRIBUTION		
SANTA FE		
FILE	<u> </u>	
U.S.G.S.		L
LAND OFFICE		
DESEATOR	T	i

CONDITIONS OF APPROVAL, IF ANY:

OIL CONSERVATION DIVISION P. O. BOX 2088

Form C-103 Revised 19-1-78

SANTA FE. NEW MEXICO 87501	
FILE	5a. Indicate Type of Lease
U.S.G.S.	State Fee X
DPERATOR	5. State Oil & Gas Lease No.
SUNDRY NOTICES AND REPORTS ON WELLS	
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG SACK TO A DIFFERENT RESERVOIR.	
	7. Unit Agreement Name
OIL A GAS WELL OTHER.	S Format Land Name
. Name of Operator	8. Form or Lease Name
Amoro Production Comfant	South Hobbs (GSA) UNIT
1. Address of Operator	
P. O. Box 3092 HOUSTON IX 77253	223
1. Location of Well	Hobbs GSA
UNIT LETTER N 1791 PEET PROM THE WEST LINE AND 1257 PEET PRO	THINK THE THE THE
THE South LINE, SECTION 34 TOWNSHIP 18-5 RANGE 38-E NMP	
15. Elevation (Show whether DF, RT, GR, etc.)	12. County
3620.3 GR	LEA MININ
Check Appropriate Box to indicate Matare of Notice, report of	NT REPORT OF: .
NOTICE OF INTENTION TO: SUBSEQUE	THE REPORT OF .
PLUS AND ASANDON REMEDIAL WORK	ALTERING CABING
PERFORM REMEDIAL WORK	PLUS AND ABANDONMENT
TEMPORARILY ASARDON CASING TEST AND CEMENT JOS	
OTHER CABING OTHER COmplete as	A producer X
DYNER	
17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including the pertinent dates, including the pertinent dates.	ng estimated date of starting any proposed
work) SEE RULE 1703. RIVER RIT AND Drill CEMENT AND CLEAN	out to 4217'.
work) SEE RULE 1703. RIVER RIT AND Drill CEMENT AND CLEAN	out to 4217'.
1500 DST AND TEST OR, KUN CBL FR	out to 4217'.
MI AND RUSU. RUN BIT AND Drill cement AND clean Test casing to 1500 PSI AND test OK, Run CBL FR	out to 4217'. com 4212 to Surface. 090' with 4 JSPF.
MI AND RUSU. RUN BIT AND Drill cement AND clean Test casing to 1500 PSI AND test OK, Run CBL FR	out to 4217'. com 4212 to Surface. 090' with 4 JSPF.
MI AND RUSU. RUN BIT AND Drill cement AND clean MI AND RUSU. RUN BIT AND Drill cement AND clean Test casing to 1500 PSI AND test OK, RUN CBL FR RUN 4" casing gun AND Perforate from 4050' to 4090' will	out to 42/7'. com 42/2 to Surface. 090' with 4 JSPF. th 2300 9ALS 20%
MI AND RUSU. RUN BIT AND Drill cement AND clean MI AND RUSU. RUN BIT AND Drill cement AND clean Test casing to 1500 PSI AND test OK, RUN CBL FR RUN 4" casing gun AND Perforate from 4050' to 4090' will	out to 4217'. com 4212 to Surface. 090' with 4 JSPF. to 2300 9ALS 20%
MI AND RUSU. RUN BIT AND Drill cement AND clean MI AND RUSU. RUN BIT AND Drill cement AND clean Test casing to 1500 PSI AND test OK, RUN CBL FR RUN 4" casing gun And Perforate from 4050' to 4 RUN PPI PACKER AND ACIDIZE From 4060' to 4090' will NE HCL. RUN ESP AND 3'12" Tubing to 4014'. RD	out to 4217'. EDM 4212 to Surface. 090' with 4 JSPF. 1 2300 GALS 20% AND MOSU 12-12-88
MI AND RUSU. RUN BIT AND Drill cement AND clean MI AND RUSU. RUN BIT AND Drill cement AND clean Test casing to 1500 PSI AND test OK, RUN CBL FR RUN 4" casing gun And Perforate from 4050' to 4 RUN PPI PACKER AND ACIDIZE From 4060' to 4090' will NE HCL. RUN ESP AND 3'12" Tubing to 4014'. RD	out to 4217'. com 4212 to Surface. 090' with 4 JSPF. 1 2300 gals 20% AND MOSU 12-12-88
MI AND RUSU. RUN BIT AND Drill cement AND clean MI AND RUSU. RUN BIT AND Drill cement AND clean Test casing to 1500 PSI AND test OK, RUN CBL FR RUN 4" casing gun AND Perforate from 4050' to 4090' will	out to 4217'. com 4212 to Surface. 090' with 4 JSPF. 1 2300 gals 20% AND MOSU 12-12-88
MI AND RUSU. RUN BIT AND Drill cement AND clean MI AND RUSU. RUN BIT AND Drill cement AND clean Test casing to 1500 PSI AND test OK, RUN CBL FR RUN 4" casing gun And Perforate from 4050' to 4 RUN PPI PACKER AND ACIDIZE From 4060' to 4090' will NE HCL. RUN ESP AND 3'12" Tubing to 4014'. RD	out to 4217'. com 4212 to Surface. 090' with 4 JSPF. 1 2300 gals 20% AND MOSU 12-12-88
MI AND RUSU. RUN BIT AND Drill cement AND clean MI AND RUSU. RUN BIT AND Drill cement AND clean Test casing to 1500 PSI AND test OK, RUN CBL FR RUN 4" casing gun And Perforate from 4050' to 4 RUN PPI PACKER AND ACIDIZE From 4060' to 4090' will NE HCL. RUN ESP AND 3'12" Tubing to 4014'. RD	out to 4217'. com 4212 to Surface. 090' with 4 JSPF. 1 2300 gals 20% AND MOSU 12-12-88
MI AND RUSU. RUN BIT AND Drill cement AND clean MI AND RUSU. RUN BIT AND Drill cement AND clean Test casing to 1500 PSI AND test OK, RUN CBL FR RUN 4" casing gun And Perforate from 4050' to 4 RUN PPI PACKER AND ACIDIZE From 4060' to 4090' will NE HCL. RUN ESP AND 3'12" Tubing to 4014'. RD	out to 4217'. com 4212 to Surface. 090' with 4 JSPF. 1 2300 gals 20% AND MOSU 12-12-88
MI AND RUSU. RUN BIT AND Drill cement AND clean MI AND RUSU. RUN BIT AND Drill cement AND clean Test casing to 1500 PSI AND test OK, RUN CBL FR RUN 4" casing gun And Perforate from 4050' to 4 RUN PPI PACKER AND ACIDIZE From 4060' to 4090' will NE HCL. RUN ESP AND 3'12" Tubing to 4014'. RD	out to 4217'. com 4212 to Surface. 090' with 4 JSPF. 1 2300 gals 20% AND MOSU 12-12-88
MI AND RUSU. RUN BIT AND Drill cement AND clean MI AND RUSU. RUN BIT AND Drill cement AND clean Test casing to 1500 PSI AND test OK, RUN CBL FR RUN 4" casing gun And Perforate from 4050' to 4 RUN PPI PACKER AND ACIDIZE From 4060' to 4090' will NE HCL. RUN ESP AND 3'12" Tubing to 4014'. RD	out to 4217'. com 4212 to Surface. 090' with 4 JSPF. 1 2300 gals 20% AND MOSU 12-12-88
MI AND RUSU. RUN BIT AND Drill cement AND clean MI AND RUSU. RUN BIT AND Drill cement AND clean Test casing to 1500 PSI AND test OK, RUN CBL FR RUN 4" casing gun And Perforate from 4050' to 4 RUN PPI PACKER AND ACIDIZE From 4060' to 4090' will NE HCL. RUN ESP AND 3'12" Tubing to 4014'. RD	out to 4217'. com 4212 to Surface. 090' with 4 JSPF. 1 2300 gals 20% AND MOSU 12-12-88
MI AND RUSU. RUN BIT AND Drill cement AND clean MI AND RUSU. RUN BIT AND Drill cement AND clean Test casing to 1500 PSI AND test OK, RUN CBL FR RUN 4" casing gun And Perforate from 4050' to 4 RUN PPI PACKER AND ACIDIZE From 4060' to 4090' will NE HCL. RUN ESP AND 3'12" Tubing to 4014'. RD	out to 4217'. com 4212 to Surface. 090' with 4 JSPF. 1 2300 gals 20% AND MOSU 12-12-88
MI AND RUSU. RUN BIT AND Drill cement AND clean MI AND RUSU. RUN BIT AND Drill cement AND clean Test casing to 1500 PSI AND test OK, RUN CBL FR RUN 4" casing gun And Perforate from 4050' to 4 RUN PPI PACKER AND ACIDIZE From 4060' to 4090' will NE HCL. RUN ESP AND 3'12" Tubing to 4014'. RD	out to 4217'. com 4212 to Surface. 090' with 4 JSPF. 1 2300 gals 20% AND MOSU 12-12-88
MI AND RUSU. RUN BIT AND Drill cement And clean TEST CASING to 1500 PSI AND test OK, RUN CBL FR RUN 4" casing gun And Perforate from 4050' to 4 RUN PPI PACKER AND ACIDIZE FROM 4060' to 4090' will NE HCL. RUN ESP AND 3'Iz' Tubing to 4014'. RD IP: 16.5 BBL OIL, 1297 BBL WATER, 136 MG	out to 4217'. com 4212 to Surface. 090' with 4 JSPF. 1 2300 gals 20% AND MOSU 12-12-88
MI AND RUSU. RUN BIT AND Drill cement AND clean MI AND RUSU. RUN BIT AND Drill cement AND clean Test casing to 1500 PSI AND test OK, RUN CBL FR RUN 4" casing gun And Perforate from 4050' to 4 RUN PPI PACKER AND ACIDIZE From 4060' to 4090' will NE HCL. RUN ESP AND 3'12" Tubing to 4014'. RD	OUT to 4217'. EDM 4212 to Surface. 090' WITH 4 JSPF. TO 2300 GALS 20% AND MOSU 12-12-88
MI AND RUSU. RUN BIT AND Drill cement And clean TEST CASING to 1500 PSI AND test OK, RUN CBL FR RUN 4" casing gun And Perforate from 4050' to 4 RUN PPI PACKER AND ACIDIZE FROM 4060' to 4090' will NE HCL. RUN ESP AND 3'Iz' Tubing to 4014'. RD IP: 16.5 BBL OIL, 1297 BBL WATER, 136 MG	out to 4217'. com 4212 to Surface. 090' with 4 JSPF. 1 2300 gals 20% AND MOSU 12-12-88
MI AND RUSU. RUN BIT AND Drill cement AND clean TEST CASING to 1500 PSI AND test OK, RUN CBL FR RUN 4" Casing gun And Perforate from 4050' to 4 RUN PPI PACKER AND ACIDIZE From 4060' to 4090' will NE HCL. RUN ESP AND 3" 2" Tubing to 4014'. RD IP: 16.5 BBL OIL, 1297 BBL WATER, 136 MI 18.1 hereby certify that the information above is true and complete to the best of my knowledge and belief. BI. Steele TITLE KUMIN AUALYST	OUT to 4217'. EDM 4212 to Surface. 090' WITH 4 JSPF. TO 2300 GALS 20% AND MOSU 12-12-88 CF DATE 4-12-89
MI AND RUSU. RUN BIT AND Drill cement And clean TEST CASING to 1500 PSI AND test OK, RUN CBL FR RUN 4" casing gun And Perforate from 4050' to 4 RUN PPI PACKER AND ACIDIZE FROM 4060' to 4090' will NE HCL. RUN ESP AND 3'Iz' Tubing to 4014'. RD IP: 16.5 BBL OIL, 1297 BBL WATER, 136 MG	OUT to 4217'. EDM 4212 to Surface. 090' WITH 4 JSPF. TO 2300 GALS 20% AND MOSU 12-12-88