

WRS COMPLETION REPORTCOMPLETIONS SEC 16 TWP 18S RGE 33E
PI# 30-T-0013 02/13/89 30-025-30499-0000 PAGE 1NMEX LEA * 510FSL 1980FWL SEC SE SW
STATE COUNTY FOOTAGE SPOTMERIDIAN OIL INC D DO
OPERATOR WELL CLASS INIT FIN5 STATE "16"
WELL NO. LEASE NAME3871KB 3858GR CORBIN W
OPER ELEV FIELD/POOL/AREALEASE TYPE NO. API 30-025-30499-0000
PERMIT OR WELL I.D. NO.11/29/1988 01/20/1989 ROTARY OIL
SPUD DATE COMP. DATE TYPE TOOL STATUS

5450 DELAWARE TMBR SHARP DRLG 27 RIG SUB 12

PROJ. DEPTH PROJ. FORM CONTRACTOR

DTD 5450 PB 5386 FM/TD DELAWARE

DRILLERS T.D. LOG T.D. PLUG BACK TD OLD T.D. FORM T.D.

LOCATION DESCRIPTION

14 MI NE HALFWAY, NM

WELL IDENTIFICATION/CHANGES

OPER CHGD FROM SOUTHLAND ROYALTY

CASING/LINER DATACSG 8 5/8 @ 350 W/ 250 SACKS
CSG 5 1/2 @ 5450 W/ 1200 SACKSTUBING DATA

TBG 2 7/8 AT 5174

INITIAL POTENTIALIPP 172BOPD 50 MCFD 116BW 24HRS
DELAWARE PERF W/ 33/IT 5184- 5244 GROSS
GTY 48.0 GOR 290

TYPE	FORMATION	LTH	TOP DEPTH/SUB	BSE DEPTH/SUB
------	-----------	-----	---------------	---------------

LOG	RUSTLER		1465 2393	
LOG	SALT		1650 2208	2870 988
LOG	YATES		3050 808	
LOG	QUEEN		4200 -342	
LOG	SN ANDRS		4818 -960	

SUBSEA MEASUREMENTS FROM GR

CONTINUED IC# 300257041088

Copyrighted 1989
Petroleum
Information Corporation**Petroleum Information****DB** a company of
The Dun & Bradstreet CorporationPI-WRS-GET
Form No 187

COMPLETIONS SEC 16 TWP 18S RGE 33E
PI# 30-T-0013 02/13/89 30-025-30499-0000 PAGE 2

MERIDIAN OIL INC D DO
5 STATE "16"

PRODUCTION TEST DATA

DELAWARE PERF W/ 33/IT 5184- 5244 GROSS
PERF 5184- 5190 5209- 5211 5222- 5244
ACID 5184- 5244 3000GALS
10% NEFE HCL
SWFR 5184- 5244 23000GALS 47000LBS SAND ADDTVGELA
X-LINK 20/40

LOGS AND SURVEYS /INTERVAL,TYPE/

LOGS CNL CBL CET

DRILLING PROGRESS DETAILS

MERIDIAN OIL INC
21 DESTA DR
MIDLAND, TX 79705
915-686-5600
11/02 LOC/1988/
12/07 DRLG 5026
12/14 5450 TD, WOCT
12/14 DEVIATION SURVEYS @ 350 (1 DEG), 858 (.25 DEG),
1310 (.75 DEG), 1312 (.25 DEG), 2308 (1.75 DEG),
2558 (2.25 DEG), 2651 (1.75 DEG), 2836 (2.50
DEG), 2891 (2 DEG), 2993 (2.50 DEG), 3055 (1.75
DEG), 3119 (1.75 DEG), 3223 (1 DEG), 3432 (1
DEG), 3717 (1 DEG), 4215 (1 DEG), 4686 (1 DEG),
4782 (1 DEG), 5026 (1 DEG), 5450 (1.50 DEG)
12/21 5450 TD, WOCT
12/27 5450 TD, WOCT
01/05 5450 TD, WOCT
01/09 5450 TD, PB 5386, PREP TREAT
01/13 5450 TD, PB 5386, TOP
02/07 TD REACHED 12/07/88 RIG REL 12/08/88
5450 TD, PB 5386
COMP 1/20/89, IPP 172 BO, 50 MCFG, 116
BWPD, GOR 290, GTY 48
PROD ZONE - DELAWARE 5184-5244
NO CORES OR DSTS RPTD