

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO. 30-025-30514
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. E-5014
7. Lease Name or Unit Agreement Name REEVES 21 STATE
8. Well No. 1
9. Production or Well Name QUEEN

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	
2. Name of Operator BASS ENTERPRISES PRODUCTION COMPANY	
3. Address of Operator P.O. BOX 2760, MIDLAND, TEXAS 79702-2760	
4. Well Location Unit Letter <u>P</u> : <u>330</u> Feet From The <u>SOUTH</u> Line and <u>660</u> Feet From The <u>EAST</u> Line Section <u>21</u> Township <u>18-S</u> Range <u>35-E</u> NMPM <u>LEA</u> County <u></u>	
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3907.3' GR.	

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: Spud date 8/11 3/4" CSG & 8 5/8" CSG. ☒
8 5 1/2" CSG.

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. 5-22-89 SPUD @ 8:00 P.M. CSDT

Drill 14 3/4" Hole to 1761'. Ran 41 JTS. 11 3/4" 42# H-40 ST&C CSG Set @ 1761'. Cemented with 750 sx Lite Tail in W/200 sx Class "C". Circ 194 sx to pit 5-24-89. WOC. 24 Hrs Test Blinds & Rams in BOPE. Drlg. Cement Plug, Float Collar & Shoe JT. 5-26-89 Drlg. 11" Hole to 3052' Ran 7 JTS. 8 5/8" 24# K-55 ST&C 49 JTS. 8 5/8" 24# J-55 ST&C & 18 JTS. 8 5/8" 28# 5-80 ST&C Casing Total of 74 JTS. CSG. Ran. Cement in Two Stages. First Stage 200 sx Halco Premium Plus Thixotropic (14.8 ppg.) 1.45 FT 3/sx Plug Down @ 4:10 A.M. CDT 5-27-89. Second Stage W/400 sx Class "C" W/2% CaCl 2(1.32 Ft 3/sx 14.8 PPG.) Plug Down @ 7:15 A.M. CDT. CIRC 45 sx to Surface. Test BOPE. 5-28-89 Test Blind Rams Choke Manifold to 1000 PSI Test pipe Rams & BOP to 1000 PSI. Drlg DV Tool, Cement, Float Collar, Drlg. 7 7/8" Hole 5/29/89. Drld. 7 7/8" Hole to 4565' 6-1-89 Ran 67 JTS. 5 1/2" 14# K-55 ST&C CSG. & 45 JTS. 5 1/2" 14# J-55 ST&C CSG. DV Tool Set @ 3118.70 Cemented 5 1/2" CSG. in Two Stages, First Stage: Cemented W/350 sx HOWCO Lite @ 1.84 Ft. 3/sx 12.7 ppg. & 200 sx Class "C" W/2% CaCl 2 Mixed @ 1.32 Ft 3/sx 14.8 ppg. Plug Down @ 2:05 A.M. CDT. Circ 128 sx off DV Tool.

(OVER)

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE R.C. Houtchens TITLE Senior Production Clerk DATE 6-2-89

TYPE OR PRINT NAME R.C. Houtchens TELEPHONE NO. 915-688-3300

(This space for State Use)

Orig. Signed by
Paul Kautz
Geologist

APPROVED BY _____ TITLE _____ DATE _____

CONDITIONS OF APPROVAL, IF ANY:

JUN 9 1989

Second Stage: Cemented 160 sx HOWCO Lite @ 1.84 Ft. 3/sx 12.7 ppg. & 300 sx "C" Neat @ 1.32 Ft. 3/sx 14.8 ppg. Plug Down @ 5:00 A.M. CDT. Released Rig @ 9:00 A.M. CDT. 6-1-89.
Will Report Completion of Form C-105 Final Report.