

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.	30 025 30595
5. Indicate Type of Lease	STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No.	K-3581-1
7. Lease Name or Unit Agreement Name	Lea 946 State
8. Well No.	4
9. Pool name or Wildcat	Buckeye <i>alt</i>

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER	2. Name of Operator Hondo Oil & Gas Company
3. Address of Operator P. O. Box 2208, Roswell, NM 88202	4. Well Location Unit Letter <u>G</u> : <u>2307</u> Feet From The <u>North</u> Line and <u>1980</u> Feet From The <u>East</u> Line

Section <u>3</u>	Township <u>18S</u>	Range <u>35E</u>	NMPM	Lea	County
10. Elevation (Show whether DF, RKB, RT, GR, etc.) 3905' GR					

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
OTHER: <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
	CASING TEST AND CEMENT JOB <input type="checkbox"/>
	OTHER: <input type="checkbox"/>

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

We plan to plug this well as follows:

- (1) set CIBP 100' above the top perforation or @ 8054' with 35' of cement on top
- (2) cut and pull 5 1/2" casing @ 7000'
- (3) cement 5 1/2" casing stub with 50' of cement in and out of stub and tag cement
- (4) set open hole bridge plug with 100' cement plug at the top of the San Andres which is 4380'
- (5) set 100' cement plug across 8 5/8" casing and tag cement
- (6) set 100' cement plug at the top of the Salt which is 1955'
- (7) set 10 sx. cement surface plug
- (8) cut off wellhead and install dry hole marker

Plugging procedure per Paul Kautz, NMOCD-Hobbs District Office.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE E. L. Buttross Jr. TITLE Petroleum Engineer DATE 4/4/90
TYPE OR PRINT NAME E. L. Buttross, Jr. (505) TELEPHONE NO. 625-6732

(This space for State Use)

APPROVED BY _____ TITLE _____ DATE _____
CONDITIONS OF APPROVAL, IF ANY: