

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

SUBMIT IN TRIPLICATE
(Other copies to be submitted to the appropriate agency.)

Form approved.
Budget Bureau No. 1004-013
Expires August 31, 1985

5. LEASE DESIGNATION AND SERIAL NO.

NM 65970

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT" for such proposals.)

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR
Yates Petroleum Corporation

3. ADDRESS OF OPERATOR
105 South 4th St., Artesia, NM 88210

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.*
See also space 17 below.)
At surface
330' FSL & 330' FEL, Sec. 17-T19S-R32E

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Aqueduct AGG Federal

9. WELL NO.

1

10. FIELD AND POOL, OR WILDCAT

Und. West Lusk Delaware

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Unit P, Sec. 17-19S-32E

12. COUNTY OR PARISH 13. STATE

API #30-025-30597 3594.5' GR Lea NM

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☐

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐
Production Casing, Perforate ☒

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.) *

TD 7300'. Reached TD 4:30 AM 6-28-89. Ran 175 joints 5-1/2" 15.5# J-55 LT&C casing set 7300'. Guide shoe set 7300', float collar set 7258'. Marker joints set 6988' and 6420'. Cemented w/500 gals Excell gel, 500 gals Surebond, 975 sx Class "H" with 10#/sx Salt (yield 1.23, wt 15.6). PD 8:00 AM 6-29-89. Bumped plug to 2500 psi for 5 minutes, float and casing held okay. WOC.
7-12-89. Perforated 6486-6498' w/12 - .42" holes as follows: 6486, 87, 88, 89, 90, 92, 93, 94, 95, 96, 97 and 6498'. Acidized perfs 6486-98' w/1500 gals 15% NEFE acid and ball sealers.

RECEIVED

18. I hereby certify that the foregoing is true and correct

SIGNED *Janita Doodler*

TITLE Production Supervisor

DATE 7-18-89

(This space for Federal or State office use)

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

*See Instructions on Reverse Side